

UNIVA

UNIVA CORPORATION

GRID ENGINE DOCUMENTATION

Grid Engine Release Notes

Author:
Univa Engineering

Version:
8.6.5

May 6, 2019

Contents

1	License	1
2	Supported Operating Systems, Versions and Architectures	5
3	Supported and Tested Docker Versions	7
3.1	Known Docker Issues That Affect Univa Grid Engine	12
4	Fixes and Enhancements	13
4.1	Major Enhancements	13
4.1.1	(UGE 8.6.5) Support for Linux Mount Namespace	13
4.1.2	(UGE 8.6.3) Bulk Changes for Exec Hosts and Projects	13
4.1.3	New Core Binding Strategies and PE Behavior	13
4.1.4	Affinity Based Job Placement	14
4.1.5	Managing Access to Devices with RSMAPs	15
4.1.6	Integration with Nvidia DCGM	15
4.1.7	Performance Improvements	16
4.1.8	Reworked Dispatch Job Information	17
4.1.9	Data Compression at Communication Layer	17
4.1.10	Using RSMAPs with Topology Masks and XOR Operator	18
4.2	Other	19
4.2.1	JSV Improvements	19
4.2.2	Reduce qhost Data Request Sizes at sge_qmaster	20
4.2.3	Upgrade Advance and Standing Reservations	20
4.2.4	<code>per_pe_task_prolog</code> and <code>per_pe_task_epilog</code>	20
4.2.5	Support for nvidia-docker 2.0	20
4.2.6	The Master Task of a Parallel Docker Job in a Container	20
4.2.7	Run the Container as root, Allow to Run Prolog etc. as a Different User .	21
4.2.8	Automatically Map User ID and Group ID of a User Into the Container .	21
4.2.9	Create a <code>container_pe_hostfile</code> with all Container Hostnames	21
4.2.10	Docker Daemon Response Timeout	22
4.2.11	Cgroups and Containers	22
4.2.12	Specify Arguments to Autostart Docker Jobs	22

4.2.13	New Client Command qralter	22
4.2.14	Changes to the loadcheck Command	23
4.2.15	Changed startup behaviour of the execution daemon	23
4.2.16	Forwarding the environment for a qrsh (without command) and qlogin job is enabled	23
4.2.17	Suppress the user switch inside Docker jobs	23
4.2.18	Allow to skip Docker image check in execution daemon	24
4.2.19	New values for initial_state of a queue	24
4.2.20	Removed reporting of m_mem_free_nX load values	24
4.2.21	GPU Affinity as Soft Request	24
4.3	Full List of Fixes and Enhancements	25
4.3.1	8.6.0 (and Also Fixed for a 8.5.*, 8.4.*, 8.3.* Patch Release)	25
4.3.2	8.6.0 (and Also Fixed for a 8.5.* and 8.4.* Patch Release)	25
4.3.3	8.6.0 (and Also Fixed for a 8.5.* Patch Release)	26
4.3.4	8.6.0	30
4.3.5	8.6.1	36
4.3.6	8.6.2	36
4.3.7	8.6.3	36
4.3.8	8.6.4	37
4.3.9	8.6.5prealpha_devbuild_1	38
4.3.10	8.6.5prealpha_devbuild_2	40
4.3.11	8.6.5prealpha_devbuild_3	41
4.3.12	8.6.5alpha1	41
4.3.13	8.6.5alpha2	42
5	Upgrade Notes	43
5.1	Upgrade Requirements	43
6	Compatibility Notes	44
6.1	Changes in Windows Execution Host sgepasswd File	44
6.2	Scheduler Log File	44
6.3	Removed Scheduler-Parameter queue_sort_method	44
6.4	Changes for qconf Exit States	45
6.5	Changes for Scheduler Profiling	45

6.6	Changed Limit Calculations	45
6.7	New Default for Job Verification of DRMAA Submitted Jobs	46
6.8	Default for Integer Complexes	46
6.9	Deprecated Functionality	47
6.10	Removed Functionality	47
6.11	Changed UGERest configuration location	47
7	Known Issues and Limitations	47

1 License

TERM SOFTWARE LICENSE AGREEMENT

This agreement is between the individual or entity agreeing to this agreement and Univa Corporation, a Delaware corporation (Univa) with its registered office at 2300 N Barrington Road, Suite 400, Hoffman Estates, IL 60195.

1. SCOPE

This agreement governs the licensing of the Univa Software and Support provided to Customer.

- Univa Software means the Univa software described in the order, all updates and enhancements provided under Support, its software documentation, and license keys (Univa Software), which are licensed under this agreement. This Univa Software is only licensed and is not sold to Company.
- Third-Party Software/Open Source Software licensing terms are addressed on the bottom of this agreement.

2. LICENSE

Subject to the other terms of this agreement, Univa grants Customer, under an order, a non-exclusive, non-transferable, renewable term license up to the license capacity purchased to: (a) Operate the Univa Software in Customer's business operations; and (b) Make a reasonable number of copies of the Univa Software for archival and backup purposes. Customer's contractors and majority owned affiliates are allowed to use and access the Univa Software under the terms of this agreement. Customer is responsible for their compliance with the terms of this agreement. The initial contracted term of this license will be automatically renewed on its expiry for a one year period unless a written notification of termination has been received 60 days prior to term expiry.

3. RESTRICTIONS

Univa reserves all rights not expressly granted. Customer is prohibited from: (a) assigning, sublicensing, or renting the Univa Software or using it as any type of software service provider or outsourcing environment; or (b) causing or permitting the reverse engineering (except to the extent expressly permitted by applicable law despite this limitation), decompiling, disassembly, modification, translation, attempting to discover the source code of the Univa Software or to create derivative works from the Univa Software.

4. PROPRIETARY RIGHTS AND CONFIDENTIALITY

- (a) Proprietary Rights. The Univa Software, workflow processes, designs, know-how and other technologies provided by Univa as part of the Univa Software are the proprietary property of Univa and its licensors, and all right, title and interest in and to such items, including all associated intellectual property rights, remain only with Univa. The Univa Software is protected by applicable copyright, trade secret, and other intellectual property laws. Customer may not remove any product identification, copyright, trademark or other notice from the Univa Software.

- (b) Confidentiality. Recipient may not disclose Confidential Information of Discloser to any third party or use the Confidential Information in violation of this agreement.
- (c) Confidential Information means all proprietary or confidential information that is disclosed to the recipient (Recipient) by the discloser (Discloser), and includes, among other things:
 - any and all information relating to Univa Software or Support provided by a Discloser, its financial information, software code, flow charts, techniques, specifications, development and marketing plans, strategies, and forecasts;
 - as to Univa the Univa Software and the terms of this agreement (including without limitation, pricing information).

(ii) Confidential Information excludes information that:

- was rightfully in Recipient's possession without any obligation of confidentiality before receipt from the Discloser;
- is or becomes a matter of public knowledge through no fault of Recipient;
- is rightfully received by Recipient from a third party without violation of a duty of confidentiality;
- is independently developed by or for Recipient without use or access to the Confidential Information; or is licensed under an open source license. Customer acknowledges that any misuse or threatened misuse of the Univa Software may cause immediately irreparable harm to Univa for which there is no adequate remedy at law. Univa may seek immediate injunctive relief in such event.

5. PAYMENT

Customer will pay all fees due under an order within 30 days of the invoice date, plus applicable sales, use and other similar taxes.

6. WARRANTY DISCLAIMER. UNIVA DISCLAIMS ALL EXPRESS AND IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION THE IMPLIED WARRANTY OF TITLE, MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE UNIVA SOFTWARE MAY NOT BE ERROR FREE, AND USE MAY BE INTERRUPTED.

7. TERMINATION

Either party may terminate this agreement upon a material breach of the other party after a 30 days notice/cure period, if the breach is not cured during such time period. Upon termination of this agreement or expiration of an order, Customer must discontinue using the Univa Software, de-install it and destroy or return the Univa Software and all copies, within 5 days. Upon Univa's request, Customer will provide written certification of such compliance.

8. SUPPORT INCLUDED

Univa's technical support and maintenance services (Support) is included with the fees paid under an order. Univa may change its Support terms, but Support will not materially degrade during any paid term. More details on Support are located at www.univa.com/support

9. LIMITATION OF LIABILITY AND DISCLAIMER OF DAMAGES

There may be situations in which, as a result of material breach or other liability, Customer is entitled to make a claim for damages against Univa. In each situation (regardless of the form of the legal action (e.g. contract or tort claims)), Univa is not responsible beyond: (a) the amount of any direct damages up to the amount paid by Customer to Univa in the prior 12 months under this agreement; and (b) damages for bodily injury (including death), and physical damage to tangible property, to the extent caused by the gross negligence or willful misconduct of Univa employees while at Customer's facility. Other than for breach of the Confidentiality section by a party, the infringement indemnity, violation of Univa's intellectual property rights by Customer, or for breach of Section 2 by Customer, in no circumstances is either party responsible for any (even if it knows of the possibility of such damage or loss): (a) loss of (including any loss of use), or damage to: data, information or hardware; (b) lost profits, business, or goodwill; or (c) other special, consequential, or indirect damages

10. INTELLECTUAL PROPERTY INDEMNITY

If a third-party claims that Customer's use of the Univa Software under the terms of this agreement infringes that party's patent, copyright or other proprietary right, Univa will defend Customer against that claim at Univa's expense and pay all costs, damages, and attorney's fees, that a court finally awards or that are included in a settlement approved by Univa, provided that Customer: (a) promptly notifies Univa in writing of the claim; and (b) allows Univa to control, and cooperates with Univa in, the defense and any related settlement. If such a claim is made, Univa could continue to enable Customer to use the Univa Software or to modify it. If Univa determines that these alternatives are not reasonably available, Univa may terminate the license to the Univa Software and refund any unused fees. Univa's obligations above do not apply if the infringement claim is based on the use of the Univa Software in combination with products not supplied or approved by Univa in writing or in the Univa Software, or Customer's failure to use any updates within a reasonable time after such updates are made available. This section contains Customer's exclusive remedies and Univa's sole liability for infringement claims.

11. GOVERNING LAW AND EXCLUSIVE FORUM

This agreement is governed by the laws of the State of Illinois, without regard to conflict of law principles. Any dispute arising out of or related to this agreement may only be brought in the state of Illinois. Customer consents to the personal jurisdiction of such courts and waives any claim that it is an inconvenient forum. The prevailing party in litigation is entitled to recover its attorneys' fees and costs from the other party.

12. MISCELLANEOUS

- (a) Inspection. Upon request by Univa, Customer must provide a usage report at least 60 days before the renewal anniversary. Univa, or its representative, may audit Customer's usage of the Univa Software at any Customer facility. Customer will cooperate with such audit. Customer agrees to pay within 30 days of written notification any fees applicable to Customer's use of the Univa Software in excess of the license.

- (b) Entire Agreement. This agreement, and all orders, constitute the entire agreement between the parties, and supersedes all prior or contemporaneous negotiations, representations or agreements, whether oral or written, related to this subject matter.
- (c) Modification Only in Writing. No modification or waiver of any term of this agreement is effective unless signed by both parties.
- (d) Non-Assignment. Neither party may assign or transfer this agreement to a third party, except that the agreement and all orders may be assigned upon notice as part of a merger, or sale of all or substantially all of the business or assets, of a party.
- (e) Export Compliance. Customer must comply with all applicable export control laws of the United States, foreign jurisdictions and other applicable laws and regulations.
- (f) US Government Restricted Rights. The Univa Software is provided with RESTRICTED RIGHTS. Use, duplication, or disclosure by the U.S. government or any agency thereof is subject to restrictions as set forth in subparagraph (c)(I)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.227-7013 or subparagraphs (c)(1) and (2) of the Commercial Computer Software Restricted Rights at 48 C.F.R. 52.227-19, as applicable.
- (g) Independent Contractors. The parties are independent contractors with respect to each other.
- (h) Enforceability. If any term of this agreement is invalid or unenforceable, the other terms remain in effect.
- (i) No PO Terms. Univa rejects additional or conflicting terms of a Customer's form-purchasing document.
- (j) No CISG. The United Nations Convention on Contracts for the International Sale of Goods does not apply.
- (k) Survival. All terms that by their nature survive termination or expiration of this agreement, will survive.

Additional software specific licensing terms: Grid Engine and Univa Software incorporate certain third-party software listed at the URL below. These licenses are accepted by use of the software and may represent license grants with restrictions which Univa is bound to provide. We are hereby notifying you of these licenses. * Third Party Software means certain third-party software which is provided along with the Univa Software, and such software is licensed under the license terms located at: <http://www.univa.com/resources/licenses/> * Open Source Software means certain opens source software which is provided along with the Univa Software, and such software is licensed under the license terms located at: <http://www.univa.com/resources/licenses/>

Rev: Jun 2018

2 Supported Operating Systems, Versions and Architectures

Univa Grid Engine supports various platforms, hardware architectures and versions of operating systems. Find the full list in following table:

Operating System	Version	Architecture
SLES	11, 12	x86, x86-64
RHEL	6	x86, x86-64
	7 and higher	x86, x86-64, Power8/9
CentOS	6	x86, x86-64
	7 and higher	x86, x86-64, Power8/9
Oracle Linux	6 or higher, 7	x86, x86-64
Ubuntu	10.04LTS - 18.04LTS	x86, x86-64
Oracle Solaris	10, 11	x86-64, SPARC 64bit
HP-UX	11.0 or higher	64bit
IBM AIX	7.1 or later	64bit
macOS	10.11 or higher	x86, x86-64
Microsoft Windows	XP Professional (SP3)	32 bit
Microsoft Windows	Server 2003 / 2003 R2	32 bit
Microsoft Windows	Vista Enterprise / Ultimate	32 and 64bit
Microsoft Windows	Server 2008 / 2008 R2	32 and 64bit
Microsoft Windows	7 Professional / Enterprise / Ultimate	32 and 64bit
Microsoft Windows	Server 2012 / 2012 R2	32 and 64bit
Microsoft Windows	8 / 8.1 Pro / Enterprise	32 and 64bit
Microsoft Windows	10 Pro / Enterprise	32 and 64bit

Table 1: Supported Operating Systems, Versions and Architectures

PLEASE NOTE: Hosts running the Microsoft Windows operating system cannot be used as master or shadow hosts.

PLEASE NOTE: Univa Grid Engine qmaster is fully supported on Linux and Solaris. We provide binaries in Univa Grid Engine for running the qmaster on other operating systems but they are not supported and delivered as a courtesy. If you require qmaster support on other architectures please contact us at support@univa.com.

PLEASE NOTE:: if you require Univa Grid Engine support for older versions of the above operating systems please contact our sales or support team.

3 Supported and Tested Docker Versions

In principle, Univa Grid Engine supports these Docker versions on these Linux distributions:

Linux Distribution	Docker versions
RedHat, CentOS, Debian and Ubuntu	1.12.0 to 1.13.0 and 17.03.0-ce to 17.12.0-ce
SLES and openSUSE	1.12.0 to 1.13.0 and 17.03.0-ce to 17.09.1-ce

But in the past some Docker versions did not work properly and were withdrawn later. There were different Docker builds provided under the same version number showing a slightly different behavior, so it is not possible to ensure Univa Grid Engine does work with all Docker versions between 1.12.0 and 17.12.0. The following table shows which Docker versions were tested on which Linux distribution. The table includes the “Git commit” ID of the Docker source code, the Go language version which was used to build Docker, the build date and - for completeness - the version of the Docker RemoteAPI. Other Docker versions were not tested or are too broken to test successfully.

- Red Hat Enterprise Linux 7.4 (Maipo), Kernel 3.10.0-693.11.1.el7.x86_64

Docker	Git commit	Go	Build date	API	containerd
1.12.0	8eab29e	go1.6.3		1.24	
1.12.1	23cf638	go1.6.3		1.24	
1.12.2	bb80604	go1.6.3		1.24	
1.12.3	6b644ec	go1.6.3		1.24	
1.12.4	1564f02	go1.6.4	Mon Dec 12 23:41:49 2016	1.24	
1.12.5	7392c3b	go1.6.4	Fri Dec 16 02:23:59 2016	1.24	
1.12.6	78d1802	go1.6.4	Tue Jan 10 20:20:01 2017	1.24	
1.13.0	49bf474	go1.7.3	Tue Jan 17 09:55:28 2017	1.25	
17.03.0-ce	3a232c8	go1.7.5	Tue Feb 28 08:10:07 2017	1.26	
17.03.1-ce	c6d412e	go1.7.5	Mon Mar 27 17:05:44 2017	1.27	
17.03.2-ce	f5ec1e2	go1.7.5	Tue Jun 27 02:21:36 2017	1.27	
17.06.2-ce	cec0b72	go1.8.3	Tue Sep 5 20:00:25 2017	1.30	
17.07.0-ce	8784753	go1.8.3	Tue Aug 29 17:43:23 2017	1.31	
17.09.0-ce	afdb6d4	go1.8.3	Tue Sep 26 22:42:49 2017	1.32	
17.09.1-ce	19e2cf6	go1.8.3	Thu Dec 7 22:25:03 2017	1.32	

Docker	Git commit	Go	Build date	API	containerd
17.12.0-ce	c97c6d6	go1.9.2	Wed Dec 27 20:12:46 2017	1.35	
18.03.0-ce	0520e24	go1.9.4	Wed Mar 21 23:13:03 2018	1.37	
18.03.1-ce	9ee9f40	go1.9.5	Thu Apr 26 07:23:58 2018	1.37	
18.06.0-ce	0ffa825	go1.10.3	Wed Jul 18 19:10:42 2018	1.38	
18.06.1-ce	e68fc7a	go1.10.3	Tue Aug 21 17:25:29 2018	1.38	
18.06.2-ce	6d37f41	go1.10.3	Sun Feb 10 03:48:29 2019	1.38	
18.06.3-ce	d7080c1	go1.10.3	Wed Feb 20 02:28:17 2019	1.38	
18.09.0	4d60db4	go1.10.4	Wed Nov 7 00:19:08 2018	1.39	1.2.0
18.09.1	4c52b90	go1.10.6	Wed Jan 9 19:06:30 2019	1.39	1.2.0
18.09.2	6247962	go1.10.6	Sun Feb 10 03:47:25 2019	1.39	1.2.0
18.09.3	774a1f4	go1.10.8	Thu Feb 28 06:02:24 2019	1.39	1.2.0

- CentOS 7, Kernel 3.10.0-693.2.2.el7_x86_64

Docker	Git commit	Go	Build date	API	containerd
1.12.0	8eab29e	go1.6.3		1.24	
1.12.1	23cf638	go1.6.3		1.24	
1.12.2	bb80604	go1.6.3		1.24	
1.12.3	6b644ec	go1.6.3		1.24	
1.12.4	1564f02	go1.6.4	Mon Dec 12 23:41:49 2016	1.24	
1.12.5	7392c3b	go1.6.4	Fri Dec 16 02:23:59 2016	1.24	
1.12.6	78d1802	go1.6.4	Tue Jan 10 20:20:01 2017	1.24	
1.13.0	49bf474	go1.7.3	Tue Jan 17 09:55:28 2017	1.25	
1.13.1	092cba3	go1.7.5	Web Feb 8 06:38:28 2017	1.26	
17.03.0-ce	3a232c8	go1.7.5	Tue Feb 28 08:10:07 2017	1.26	
17.03.1-ce	c6d412e	go1.7.5	Mon Mar 27 17:05:44 2017	1.27	
17.03.2-ce	f5ec1e2	go1.7.5	Tue Jun 27 02:21:36 2017	1.27	
17.06.2-ce	cec0b72	go1.8.3	Tue Sep 5 20:00:25 2017	1.30	
17.07.0-ce	8784753	go1.8.3	Tue Aug 29 17:43:23 2017	1.31	
17.09.0-ce	afdb6d4	go1.8.3	Tue Sep 26 22:42:49 2017	1.32	
17.09.1-ce	19e2cf6	go1.8.3	Thu Dec 7 22:25:03 2017	1.32	
17.12.0-ce	c97c6d6	go1.9.2	Wed Dec 27 20:12:46 2017	1.35	
18.03.0-ce	0520e24	go1.9.4	Wed Mar 21 23:13:03 2018	1.37	

Docker	Git commit	Go	Build date	API	containerd
18.03.1-ce	9ee9f40	go1.9.5	Thu Apr 26 07:23:58 2018	1.37	
18.06.0-ce	0ffa825	go1.10.3	Wed Jul 18 19:10:42 2018	1.38	
18.06.1-ce	e68fc7a	go1.10.3	Tue Aug 21 17:25:29 2018	1.38	
18.06.2-ce	6d37f41	go1.10.3	Sun Feb 10 03:48:29 2019	1.38	
18.06.3-ce	d7080c1	go1.10.3	Wed Feb 20 02:28:17 2019	1.38	
18.09.0	4d60db4	go1.10.4	Wed Nov 7 00:19:08 2018	1.39	1.2.0
18.09.1	4c52b90	go1.10.6	Wed Jan 9 19:06:30 2019	1.39	1.2.0
18.09.2	6247962	go1.10.6	Sun Feb 10 03:47:25 2019	1.39	1.2.0
18.09.3	774a1f4	go1.10.8	Thu Feb 28 06:02:24 2019	1.39	1.2.0

Note: The version 1.13.1 is the one provided by Docker. The version 1.13.1-63 provided by CentOS is broken and NOT supported by Univa Grid Engine!

- Ubuntu 16.04.3 LTS, Kernel 4.4.0-103-generic x86_64

Docker	Git commit	Go	Build date	API	containerd
1.12.0	8eab29e	go1.6.3	Thu Jul 28 22:11:10 2016	1.24	
1.12.1	23cf638	go1.6.3	Thu Aug 18 05:33:38 2016	1.24	
1.12.2	bb80604	go1.6.3	Tue Oct 11 18:29:41 2016	1.24	
1.12.3	6b644ec	go1.6.3	Wed Oct 26 22:01:48 2016	1.24	
1.12.4	1564f02	go1.6.4	Tue Dec 13 00:08:34 2016	1.24	
1.12.5	7392c3b	go1.6.4	Fri Dec 16 02:42:17 2016	1.24	
1.12.6	78d1802	go1.6.4	Tue Jan 10 20:38:45 2017	1.24	
1.13.0	49bf474	go1.7.3	Tue Jan 17 09:58:26 2017	1.25	
17.03.0-ce	3a232c8	go1.7.5	Tue Feb 28 08:01:32 2017	1.26	
17.03.1-ce	c6d412e	go1.7.5	Mon Mar 27 17:14:09 2017	1.27	
17.03.2-ce	f5ec1e2	go1.7.5	Tue Jun 27 03:35:14 2017	1.27	
17.06.2-ce	cec0b72	go1.8.3	Tue Sep 5 19:59:11 2017	1.30	
17.09.0-ce	afdb6d4	go1.8.3	Tue Sep 26 22:40:56 2017	1.32	
17.09.1-ce	19e2cf6	go1.8.3	Thu Dec 7 22:23:00 2017	1.32	
17.12.0-ce	c97c6d6	go1.9.2	Wed Dec 27 20:09:53 2017	1.35	
18.03.0-ce	0520e24	go1.9.4	Wed Mar 21 23:08:31 2018	1.37	
18.03.1-ce	9ee9f40	go1.9.5	Thu Apr 26 07:15:30 2018	1.37	

Docker	Git commit	Go	Build date	API	containerd
18.06.0-ce	Offa825	go1.10.3	Wed Jul 18 19:09:05 2018	1.38	
18.06.1-ce	e68fc7a	go1.10.3	Tue Aug 21 17:23:21 2018	1.38	
18.06.2-ce	6d37f41	go1.10.3	Sun Feb 10 03:46:30 2019	1.38	
18.06.3-ce	d7080c1	go1.10.3	Wed Feb 20 02:26:20 2019	1.38	
18.09.0	4d60db4	go1.10.4	Wed Nov 7 00:16:44 2018	1.39	1.2.0
18.09.1	4c52b90	go1.10.6	Wed Jan 9 19:02:44 2019	1.39	1.2.0
18.09.2	6247962	go1.10.6	Sun Feb 10 03:42:13 2019	1.39	1.2.2
18.09.3	774a1f4	go1.10.8	Thu Feb 28 05:59:55 2019	1.39	1.2.2

- Uuntu 16.10, Kernel 4.8.0-59-generic x86_64

Docker	Git commit	Go	Build date	API	containerd
1.13.0	49bf474	go1.7.3	Tue Jan 17 10:05:19 2017	1.25	
17.03.0-ce	3a232c8	go1.7.5	Tue Feb 28 08:05:01 2017	1.26	
17.03.1-ce	c6d412e	go1.7.5	Mon Mar 27 17:17:43 2017	1.27	
17.03.2-ce	f5ec1e2	go1.7.5	Tue Jun 27 03:59:22 2017	1.27	

- Ubuntu 17.04, Kernel 4.10.0-42-generic x86_64

Docker	Git commit	Go	Build date	API	containerd
17.09.0-ce	afdb6d4	go1.8.3	Tue Sep 26 22:41:24 2017	1.32	
17.12.0-ce	c97c6d6	go1.9.2	Wed Dec 27 20:09:19 2017	1.35	

- Ubuntu 17.10, Kernel 4.13.0-19-generic x86_64

Docker	Git commit	Go	Build date	API	containerd
17.06.2-ce	cec0b72	go1.8.3	Tue Sep 5 19:57:44 2017	1.30	
17.09.0-ce	afdb6d4	go1.8.3	Tue Sep 26 22:41:24 2017	1.32	
17.09.1-ce	19e2cf6	go1.8.3	Thu Dec 7 22:23:07 2017	1.32	
17.12.0-ce	c97c6d6	go1.9.2	Wed Dec 27 20:09:47 2017	1.35	

- Ubuntu 18.04, Kernel 4.15.0-24-generic x86_64

Docker	Git commit	Go	Build date	API	containerd
17.12.0-ce	c97c6d6	go1.9.2	Wed Dec 27 20:09:47 2017	1.35	
18.03.0-ce	0520e24	go1.9.4	Wed Mar 21 23:08:36 2018	1.37	
18.03.1-ce	9ee9f40	go1.9.5	Thu Apr 26 07:15:45 2018	1.37	

- Ubuntu 18.10, Kernel 4.18.0-15-generic x86_64

Docker	Git commit	Go	Build date	API	containerd
18.06.0-ce	Offa825	go1.10.3	Wed Jul 18 19:07:56 2018	1.38	
18.06.1-ce	e68fc7a	go1.10.3	Tue Aug 21 17:23:15 2018	1.38	
18.06.2-ce	6d37f41	go1.10.3	Sun Feb 10 03:46:20 2019	1.38	
18.06.3-ce	d7080c1	go1.10.3	Wed Feb 20 02:26:34 2019	1.38	
18.09.0	4d60db4	go1.10.4	Wed Nov 7 00:16:44 2018	1.39	1.2.0
18.09.1	4c52b90	go1.10.6	Wed Jan 9 19:02:44 2019	1.39	1.2.2
18.09.2	6247962	go1.10.6	Sun Feb 10 03:42:13 2019	1.39	1.2.2
18.09.3	774a1f4	go1.10.8	Thu Feb 28 05:59:55 2019	1.39	1.2.2

- openSUSE Leap 42.3, Kernel 4.4.92-31-default x86_64

Docker	Git commit	Go	Build date	API	containerd
1.12.0	8eab29e	go1.6.3		1.24	
1.12.1	23cf638	go1.6.3		1.24	
1.12.2	bb80604	go1.6.3		1.24	
1.12.3	6b644ec	go1.6.3		1.24	
1.12.4	1564f02	go1.6.4	Mon Dec 12 23:41:28 2016	1.24	
1.12.5	7392c3b	go1.6.4	Fri Dec 16 02:24:38 2016	1.24	
1.12.6	78d1802	go1.6.4	Tue Jan 10 20:20:13 2017	1.24	
1.13.0	49bf474	go1.7.3	Tue Jan 17 10:00:08 2017	1.25	
17.03.0-ce	60ccb22	go1.7.5	Thu Feb 23 10:55:03 2017	1.26	
17.03.1-ce	c6d412e	go1.7.5	Fri Mar 24 00:53:12 2017	1.27	
17.09.1-ce	f4ffd25	go1.8.7	Tue Jun 12 12:05:08 2018	1.32	

3.1 Known Docker Issues That Affect Univa Grid Engine

- With Docker 17.09.0-ce and Docker 17.12.0-ce, specifying the `-oom-kill-disable` switch has no effect, when using the `docker` command line client nor the `-xd` “`-oom-kill-disable`” switch of the Univa Grid Engine submit clients.

4 Fixes and Enhancements

4.1 Major Enhancements

4.1.1 (UGE 8.6.5) Support for Linux Mount Namespace

Starting with Univa Grid Engine 8.6.5 it is possible to make use of Linux mount namespaces in prolog and epilog scripts in the following way:

- create a shared base tmpdir
- enable LINUX_MOUNT_NAMESPACE execd parameter.
- create a hostgroup containing the linux hosts that support Linux mount namespaces (unshare() system call)
- create a queue that defines a common base tmpdir, prolog and epilog and use the hostgroup defined above
- run a corresponding test job

Further setup information can be found in `$SGE_ROOT/util/resources/lms/README` and examples for prolog, epilog and testing scripts are located there as well.

4.1.2 (UGE 8.6.3) Bulk Changes for Exec Hosts and Projects

Beginning with UGE 8.6.3 qconf as well as the config API will support bulk operations for the exec host and project object. Bulk operations allow to get, add, modify or delete multiple configuration objects with one UGE operation. Internal communication overhead for those operations will be reduced compared to multiple individual operations.

qconf now supports following additional switches:

- `qconf -seld [execlist]` shows a detailed list of all exec hosts or hosts in `execlist`
- `qconf -sprjld [project_list]` show a detailed list of all projects or projects in `project_list`
- `qconf -Ae dirname` adds exec hosts from every file in directory `dirname`
- `qconf -Me dirname` modifies exec hosts from every file in directory `dirname`
- `qconf -Aprj dirname` adds projects from every file in directory `dirname`
- `qconf -Mprj dirname` modifies projects from every file in directory `dirname`

4.1.3 New Core Binding Strategies and PE Behavior

For PE-jobs it is hard or even impossible to know in advance how many tasks are going to be scheduled and on how many hosts. Therefore, with Univa Grid Engine version 8.6.0, the core-binding request behavior has changed to accommodate this fact. The binding-request is now changed to a “per PE-task” request where previously it was a “per host” request. This means that the requested amount of cores for a PE-job are assigned “per PE-task”.

For example, if a job with

```
qsub -pe mype 5-7 -binding linear:2 -b y sleep 60
```

is submitted, it means that each PE-task will get 2 cores, no matter on which host or on how many hosts the tasks are scheduled.

There are now different binding-strategies, most of them exist in two versions: “host aware” and “host unaware” strategies. For example, there are two versions of linear binding strategies: `linear` and `linear_per_task`. Host unaware strategies have the suffix “`_per_task`”.

With “host aware” strategies, all tasks that end up on a host have to adhere to the given strategy together. For “host unaware” strategies, each task has to adhere to the strategy on its own. This is less strict and usually more tasks can fit on a host.

All available core binding strategies are:

```
linear:<amount>[:<socket>,<core>]
linear_per_task:<amount>
striding:<amount>:<n>[:<socket>,<core>]
striding_per_task:<amount>:<n>
explicit:[<socket>,<core>;...]<socket>,<core>
explicit_per_task:[<socket>,<core>;...]<socket>,<core>
balance_sockets:<amount>
pack_sockets:<amount>
one_socket_balance:<amount>
one_socket_per_task:<amount>
```

See man page `submit(5)` for more details and examples.

4.1.4 Affinity Based Job Placement

Univa Grid Engine 8.6.0 adds an affinity job placement policy that allows assignment to each host or queue an affinity value for each consumed resource of jobs that are running on the host or queue.

Affinity can be positive or negative. Positive affinity will attract other pending jobs, negative affinity will reject other pending jobs. Attraction/rejection will work on host and/or queue level if this is enabled by setting the weighting parameters `weight_host_affinity` and/or `weight_queue_affinity`.

Sorting based on this affinity value will cause

- affinity (so that jobs are packed on clusters of hosts or queues),
- anti-affinity (so that jobs are distributed on hosts in the cluster or queues residing on hosts)
- or best fit (if a mixture of positive and negative affinity values is defined for different resources)

Find more information concerning job placement according to affinity values in the section 3.7.1 (Host/Queue Sorting) of the Admin Guide.

4.1.5 Managing Access to Devices with RSMAPs

Univa Grid Engine 8.6.0 allows to manage access to host devices via RSMAPs. Each id of a RSMAP complex can be configured to represent a device on the host by setting the new parameter “device”. Each device can be represented by more than one RSMAP id. In the example below a RSMAP complex **gpu** is initialized with two ids and each id is mapped to a Nvidia GPU:

```
complex_values    gpu=2(gpu0[device=/dev/nvidia0] gpu1[device=/dev/nvidia1])
```

The assigned devices are shown in the qstat output of a job:

```
granted devices  host: /dev/nvidia0
```

In a default environment the configuration and assignment of devices has no effect on the scheduling, but if cgroups are available the cgroups parameter “devices” can be set to a list of devices that should be managed by Univa Grid Engine. Read/write access to all devices in the list will be blocked via cgroups and jobs will only be able to access devices that were assigned to them via RSMAPs. With the following configuration Univa Grid Engine will manage access to all Nvidia GPUs (i.e. all devices from /dev/nvidia0 to /dev/nvidia254):

```
cgroups_params  cgroup_path=/sys/fs/cgroups devices=/dev/nvidia[0-254]
```

4.1.6 Integration with Nvidia DCGM

Univa Grid Engine 8.6.0 is integrated with NVIDIA’s Data Center GPU Manager (DCGM) that provides detailed information about GPU resources.

DCGM Load Values

Support for DCGM can be enabled on host level by setting the execd parameter **UGE_DCGM_PORT** to the port DCGM uses to communicate on the specific host. If DCGM is running Univa Grid Engine will automatically retrieve load values for the installed and supported GPU devices from DCGM. For each available device the load values are reported in the format `<hostname>.cuda.<cuda_id>.<attribute>=<value>` and are visible via `qconf -se`:

```
host.cuda.0.affinity=SCTTCTTCTTCTTcttcttcttcttSCTTCTTCTTCTTcttcttcttctt,
host.cuda.0.gpu_temp=36,
host.cuda.0.mem_free=16280.000000M,
host.cuda.0.mem_total=16280.000000M,
host.cuda.0.mem_used=0.000000M,
host.cuda.0.name=Tesla P100-PCIE-16GB,
host.cuda.0.power_usage=28.527000,
host.cuda.0.verstr=390.46,
host.cuda.1.affinity=SccttcttcttcttCTTCTTCTTCTTSccttcttcttcttCTTCTTCTTCTT,
host.cuda.1.gpu_temp=40,
host.cuda.1.mem_free=16160.000000M,
host.cuda.1.mem_total=16160.000000M,
```

```

host.cuda.1.mem_used=0.000000M,
host.cuda.1.name=Tesla V100-PCIE-16GB,
host.cuda.1.power_usage=27.298000,
host.cuda.1.verstr=390.46,
host.cuda.devices=2

```

If RSMAP complexes are used to manage GPU devices, each RSMAP id can be mapped to a CUDA device with the new parameter `cuda_id`. The reported load values can then be used by UGE during the scheduling of GPU devices:

```

complex_values gpu=2(gpu0[device=/dev/nvidia0,cuda_id=0] \
                    gpu1[device=/dev/nvidia1,cuda_id=1])

```

GPU-CPU-Affinity

If DCGM is enabled, Univa Grid Engine 8.6.0 allows requesting the special load value **affinity**. If a job requests a GPU and **affinity**, it will automatically be bound to the cores that have a good affinity to the assigned GPU. This ensures that the data between the CPU and GPU is transferred in the fastest way possible. **affinity** can be requested as hard request with `-l gpu=1[affinity=1]` or `-l gpu=1[affinity=true]`, or as soft request with `-l gpu=1[affinity=2]`. If it is requested as hard request, the job will not be scheduled if Univa Grid Engine cannot find enough CPU cores needed for a GPU device. If it is requested as a soft request, Univa Grid Engine will try to schedule the job with a GPU/CPU combination with good affinity and schedule the job anyway without binding any CPU cores, if it cannot find a suitable GPU/CPU combination. If less cores are needed the request can be combined with the **-binding** switch.

The following requests a GPU device and binds the cores that have a good affinity to the assigned GPU:

```
% qsub -l gpu=1[affinity=true] -b y sleep 1000
```

4.1.7 Performance Improvements

Performance and Scalability of Univa Grid Engine has been improved in the following areas:

- general improvements affecting all components by optimizations of the Univa Grid Engine data store and updated memory allocator (jemalloc library)
- scheduler optimizations for various job profiles, esp. for parallel jobs with and without resource reservation
- higher throughput of the communication library by introducing an additional thread pool for handling incoming/outgoing data
- compression of communication data can reduce network load and avoid network saturation on slow network connections
- the impact of running many qsub -sync, drmaa or drmaa2 clients on sge_qmaster has been reduced

4.1.8 Reworked Dispatch Job Information

The mechanisms that provide Dispatch Job information have been reworked and many issues have been fixed.

qalter -w p is deprecated. Instead administrators should enable scheduler job information by setting `schedd_job_info` to `if_requested` in the scheduler configuration so that users can request dispatch job information for individual jobs via **-rdi** submit switch and make the Dispatch job information visible with **qstat -j jid**

Administrators have additional possibilities to define limits that reduce memory requirements for dispatch job information.

4.1.9 Data Compression at Communication Layer

The Univa Grid Engine communication library was enhanced to support data compression before transferring data over the network.

Large Univa Grid Engine clusters may produce high network data traffic. The network load depends mainly on cluster size and average job run times. In order to reduce the amount of data sent over the network Univa Grid Engine 8.6.0 supports data compression.

The additional effort to compress the data before sending is handled by introducing a commlib work thread pool which is also used for uncompressed data. On multi core architectures uncompressed data transfer should show a performance improvement.

Setting up the new compression mode and configure thread pool settings in Univa Grid Engine requires new configuration parameters that are specified in the following Univa Grid Engine configuration areas:

man page	Description
bootstrap(5)	New parameter <code>communication_params</code> in bootstrap file
sge_diagnostics(5)	Verify and Adjust compression and thread pool setup
sge_conf(5)	New <code>qmaster_params</code> and <code>execd_params</code> parameter <code>CL_WP_THREADS</code> for setting up work threads (overwrite bootstrap settings)
qping(1)	New compression specific output and options (see also qping enhancements section below)

Summary of changes and enhancements:

- Compression cannot be configured at Installation time. It must be enabled manually after installation or update of Univa Grid Engine.
- Univa Grid Engine 8.6.0 uses zlib for data compression - additional compression methods are planned to be supported in follow-up Univa Grid Engine releases.

- Univa Grid Engine 8.6.0 zlib compression is supported for following architectures: darwin-x64, lx-amd64, lx-arm64, lx-arm7, lx-x86, sol-amd64, sol-sparc64, sol-x86
- The **qping** binary can be used to verify compression settings.
- It is possible to enable compression only for single clients like (**qconf**, **qstat**) by setting up an environment variable (see bootstrap(5) man page).
- Compression setting changes in bootstrap configuration require a restart of Univa Grid Engine daemons.
- Commlib work pool setting changes at **sge_qmaster** and **sge_execd** can be done during runtime of the affected daemon.
- Univa Grid Engine 8.6.0 commlib modifications show a higher performance compared to older Univa Grid Engine versions if compression is not enabled; however this depends on availability of cpus on sge_qmaster host.
- Turning on compression will cause cpu overhead but dramatically reduces network traffic. Depending on the network speed individual compression settings may need to be adjusted (see sge_diagnostics(5) man page).

Also **qping** is enhanced for data compression and commlib work pool settings

- **qping -dump** shows new data compression specific columns (compressed and uncompressed message length, compression ratio and method)
- **qping -info** shows active commlib work threads and min/max settings for the requested daemon
- The sge_conf(5) qmaster_params PROF_COMMLIB_TIME now shows also the nr of active work threads used by commlib in the **sge_qmaster** messages log file.
- qping has new command line switches for basic output filtering (**-from**, **-to** and **-format**)

All these additions are described in the qping(1) man page.

4.1.10 Using RSMAPs with Topology Masks and XOR Operator

RSMAP complex attributes with topology masks and the XOR operator (^) can be combined to achieve flexible PE task placement and best application performance.

Assume the following definition of the complex attributes *gpu* and *hgpu*:

```
$ qconf -sc | egrep "#name|gpu"
#name shortcut  type    relop  requestable consumable default  urgency aapre
#-----
gpu   gpu         RSMAP  <=    YES      YES     0       0       NO
hgpu  hgpu        RSMAP  <=    YES      HOST    0       0       NO
```

Sample setting on a node on host level for *complex_values*:

2 sockets, 14 cores per socket, 28 sockets in total

```
complex_values gpu=4(0:SCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC \
1:SCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC \
```

```

                2:SCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC \
                3:SCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC) \
hgpu=4(0:SCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC \
        1:SCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC \
        2:SCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC \
        3:SCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC)

```

Assume the *allocation_rule* of the *mpi* PE is 28.

The first example reserves 4 machines with 28 slots on each machine for one hour immediately. Host level resources are only reserved in the second example (4 *hgpus* per host, 16 in total):

```

% qrsub -pe mpi 112 -d 1:0:0
% qrsub -pe mpi 112 -l hgpu=4 -d 1:0:0

```

Submit a job with 4 PE tasks on one host and request 4 *hgpus*:

```

% qsub [-ar <id>] -pe mpi 4 -par 4 -l hgpu=4

```

While only 4 queue slots on the host will be used, the topology mask of the *hgpu* resource will mark all 28 cores to be in use. If the cluster is configured that all jobs are submitted with a binding request no other jobs will be dispatched to this machine.

Schedule a job on 4 machines and get any two *gpus* on each host.

```

% qsub [-ar <id>] -pe mpi 4 -par 1 -l hgpu=2

```

A parallel job which should get the same *gpu* for each PE task on each host would be submitted as follows:

```

% qsub [-ar <id>] -pe mpi 4 -par 1 -l 'hgpu=1(^)

```

This is a shortcut for

```

% qsub [-ar <id>] -pe mpi 4 -par 1 -l 'hgpu=1(1^^2^^3^^4)

```

If the job should get the two PE tasks with one *gpu* for each task on the same socket on each host, the XOR operator can be used:

```

% qsub [-ar <id>] -pe mpi 8 -par 2 -l 'hgpu=2([0-1]^^[2-3])

```

4.2 Other

4.2.1 JSV Improvements

The Univa Grid Engine packages now contain a Python implementation for JSVs. Also new example scripts for JSV and core-binding were added

Scripts and examples can be found at “\$SGE_ROOT/util/resources/jsv”.

4.2.2 Reduce qhost Data Request Sizes at sge_qmaster

By setting the environment variable `SGE_GDI_REQUEST_REDUCE_LEVEL` it is possible to reduce the amount of data transferred from `sge_qmaster` to qhost clients. A detailed description can be found in the `qhost(1)` man page (`ENVIRONMENTAL VARIABLES`).

4.2.3 Upgrade Advance and Standing Reservations

When upgrading from Univa Grid Engine versions 8.5.4 and higher to Univa Grid Engine 8.6.0 it is now possible to upgrade advance and standing reservations as well by calling

```
# ./inst_sge -upd-ars
```

after the qmaster and execd upgrade are completed.

Prerequisite is that the host on which the upgrade is done (usually the master host) is a submit host and can resolve the user names of the AR owners and in AR `acl_list/xacl_list`.

See also the chapter about upgrading in the Installation Guide.

4.2.4 per_pe_task_prolog and per_pe_task_epilog

It is now possible to define a special prolog and epilog script that is started for each slave task of a tightly integrated parallel job that is started by `qsh -inherit`. The prolog is started before the slave task command or script, the epilog is started after it. See man page `sge_pe(5)` for details.

4.2.5 Support for nvidia-docker 2.0

NVIDIA provides the version 2.0 of their Docker Container Runtime which allows to access GPUs from within Docker containers. Univa Grid Engine now supports using this Container Runtime.

In order to make use of it, first the execution host has to be installed properly, see <https://github.com/NVIDIA/nvidia-docker>. The a job that wants to use the GPU must tell Docker to use the NVIDIA runtime by specifying the `-xd "--runtime=nvidia"` switch on the `qsub` or `qsh` command line. In order to select a specific GPU, the environment variable `NVIDIA_VISIBLE_DEVICES` must be set to for the whole container by specifying it with the `-xd "--env NVIDIA_VISIBLE_DEVICES=0"` switch.

Both the `-xd "--runtime=..."` and the `-xd "--env ..."` switch are supported since Univa Grid Engine version 8.7.0.

4.2.6 The Master Task of a Parallel Docker Job in a Container

The master task of a parallel Docker job can now be started in a container. Previously, the master task was started on the host itself but not in a container, while all slave tasks were started in containers. This new behavior requires a properly setup network, container network and DNS. See the Administrators Guide for details.

4.2.7 Run the Container as root, Allow to Run Prolog etc. as a Different User

With the `execd_params START_CONTAINER_AS_ROOT` it is now possible to start all Docker containers as root and allow the `prolog`, `pe_start`, `per_pe_task_prolog`, `per_pe_task_epilog`, `pe_stop` and `epilog` scripts to be started as a different user than the job owner. This change does not apply to “autostart Docker jobs”, i.e. jobs that specify **-b y NONE** as job script in order to use the entrypoint that is defined in the Docker image instead of using the `sge_container_shepherd` as the container entrypoint.

4.2.8 Automatically Map User ID and Group ID of a User Into the Container

If the `START_CONTAINER_AS_ROOT` parameter is set to “true”, it is now necessary that the Univa Grid Engine admin user, the job user and all pre and post script users are defined inside the container. Because this is usually not the case, by setting the `AUTOMAP_CONTAINER_USERS` parameter to “TEMPORARY”, Univa Grid Engine transfers the user ID and group ID of any of these users from the host to the container. But only Univa Grid Engine itself can use this user ID information there, it is not available for the job or any of the scripts started by Univa Grid Engine!

If `AUTOMAP_CONTAINER_USERS` is set to `PERSISTENT`, Univa Grid Engine writes an entry to the “/etc/passwd” file inside the Docker container for all these users. This allows lookup of the user information in a script, but it does not allow to switch to this user!

Caution! If `AUTOMAP_CONTAINER_USERS=PERSISTENT` is specified, if an user maps the “/etc/passwd” and “/etc/group” file into the container, the host files are modified!

4.2.9 Create a `container_pe_hostfile` with all Container Hostnames

If a parallel Docker job is started where the container hostnames are selected from RSMAPs, the execution daemon of the master task writes a `container_pe_hostfile` with all the container hostnames in the `pe_hostfile` format if the `execd_params CONTAINER_PE_HOSTFILE_COMPLEX` is set to the name of the RSMAP complex that defines the hostnames.

E.g.: If there is a RSMAP “cont_hosts” declared and on each execution host it defines values like:

```
cont_host=4(host1_cont1 host1_cont2 host1_cont3 host1_cont4)
```

and a job is submitted using

```
# qsub -pe mype 4 -l docker,docker_images="*image:latest*",cont_host=1 job_script.sh
```

and the scheduler decides to schedule the master task to host1, two slave tasks to host2 and one slave task to host3, the “`container_pe_hostfile`” might contain:

```
host1_cont3 1 <NULL> <NULL>
host2_cont1 1 <NULL> <NULL>
host2_cont4 1 <NULL> <NULL>
host3_cont2 1 <NULL> <NULL>
```

This allows to read this information in a `per_pe_task_prolog` and set the hostnames of the containers inside of the containers accordingly.

4.2.10 Docker Daemon Response Timeout

A new `execd_params DOCKER_RESPONSE_TIMEOUT` is introduced. This defines the time Univa Grid Engine waits for a response from the Docker daemon to a request Univa Grid Engine sent to the Docker daemon. This does not mean the full response must be received within the timeout; the timeout counter is reset after each character Univa Grid Engine receives from the Docker daemon in response to a specific request.

If this parameter is not specified, the default value of 60 s is used. The minimum timeout is 10 s, the maximum timeout is 86400 s. If `DOCKER_RESPONSE_TIMEOUT` is not within this range, the default value is used.

4.2.11 Cgroups and Containers

The cgroups generated by Univa Grid Engine are now used in Docker containers. There is no special configuration value, when Univa Grid Engine is configured to use cgroups, these cgroups are also used within Docker containers.

There is a known issue with cgroups and Docker that is not yet understood:

On some Linux distributions some Docker versions expects the cgroups path to contain a “slice” postfix, which makes Univa Grid Engine unable to start Docker jobs in cgroups - the jobs will fail then. This was observed on CentOS 7 with Docker 1.12.6 build c4618fb, while it was not observed with Docker 1.12.6 build 78d1802 on the same host. It was also not observed on different distributions than CentOS 7.

There are indications that it could be related to the Docker SELinux packages that are provided for CentOS 7, if they do not match the Docker version exactly, this error seems to be more likely.

4.2.12 Specify Arguments to Autostart Docker Jobs

The autostart Docker jobs, i.e. Docker jobs that were submitted as binary jobs with the keyword `NONE` as job script, now accept arguments. These arguments are provided to the binary or script defined in the `ENTRYPOINT` of the Docker image and are appended to arguments that are defined in the `ENTRYPOINT`. This works only with suitable Docker images. Whether a Docker image is suitable can be tested by manually starting

```
$ docker run -it image:latest arg1 arg2 arg3
```

on the execution host. If the script or binary defined in the `ENTRYPOINT` gets these arguments, it should also work with an Univa Grid Engine job.

4.2.13 New Client Command `qalter`

A new `qalter` client command has been added to Univa Grid Engine allowing to modify existing advance reservations, see [User Guide -> Reservations](#).

4.2.14 Changes to the loadcheck Command

loadcheck will now optionally output information about GPUs available on a host like the GPU name, available memory and cpu affinity.

loadcheck outputs a name and a value column, with Univa Grid Engine 8.6.0 the width of the name column has been increased.

4.2.15 Changed startup behaviour of the execution daemon

The execution daemon startup behaviour can be changed with Univa Grid Engine 8.6.4. Normally, if an execution daemon successfully connects to the qmaster, but does not get its configuration sent, the execution daemon quits. Usually this is the case if the execution daemon runs on a host that is not configured as execution host (yet).

By setting the environment variable “SGE_EXECD_KEEP_TRYING_TO_GET_CONFIG” to “1” before the execution daemon is started, the execution daemon stays running and periodically tries to get its configuration from the qmaster. This allows e.g. to first start the execution daemon and later configure it at the qmaster.

If “SGE_EXECD_KEEP_TRYING_TO_GET_CONFIG” is set to “0” or if it is not set, the old behaviour is in effect, i.e. the execution daemon quits if it does not get its configuration from the qmaster.

See issue GE-6235 “Provide a way to change execd startup behaviour -> infinite connection retries”

4.2.16 Forwarding the environment for a qysh (without command) and qlogin job is enabled

With Univa Grid Engine 8.6.4 and the “builtin” interactive job mechanism configured, it is now possible to forward the environment from the submit host to the job using the “-V” switch, like it is possible for “qsub” jobs all along.

4.2.17 Suppress the user switch inside Docker jobs

With Univa Grid Engine 8.6.4 it is now possible to start an autostart Docker job as the user that is defined in the Docker image the container the job uses is created from. In order to allow this, the Univa Grid Engine administrator must configure the “qmaster_params” “ENABLE_XD_RUN_AS_IMAGE_USER=1” (see `sge_conf(5)`) to allow the users to submit a job with the option “-xd_run_as_image_user y[es]|n[o]” (see `submit(1)`).

With this option, an autostart Docker job (i.e. a Docker job that has no job script argument, but the keyword “NONE” instead) is started as the user that is defined in the Docker image specified in the job submit command line.

4.2.18 Allow to skip Docker image check in execution daemon

With Univa Grid Engine 8.6.4, a boolean “execd_params” “DOCKER_SKIP_IMAGE_CHECK” was added. If it is set to 1 or TRUE the check if the image for a hard requested docker_images request actually exists is skipped.

See sge_conf(5) for details.

4.2.19 New values for initial_state of a queue

With Univa Grid Engine 8.6.4, the new possible values “execd_enabled” and “execd_disabled” have been added for the initial_state parameter of a queue. If set to any of these values, the queue will only be enabled/disabled when the execd is (re-)started, not when qmaster is restarted. The current behaviour if the parameter is set to “disabled” and “enabled” was not changed.

4.2.20 Removed reporting of m_mem_free_nX load values

With Univa Grid Engine 8.6.5, reporting of m_mem_free_nX (i.e. m_mem_free_n0, m_mem_free_n1, ..) as well as m_mem_used_nX as loadvalues has been removed. The reason for this change is the lack of information provided by the Linux kernel about Buffers and Caches on NUMA nodes. This can lead to drastically lower values being reported than what is actually available, thus prohibiting jobs from being scheduled onto such a host. Since there is currently no way to report memory values that are at least approximately close to reality, none will be reported.

m_mem_total_nX are still going to be reported.

4.2.21 GPU Affinity as Soft Request

With Univa Grid Engine 8.6.5, GPU affinity for jobs that request GPUs via RSMAPs can be requested as a soft request with -l GPU=1[affinity=2]. If a job requests GPUs and affinity as soft request, Univa Grid Engine will try to find and assign a CPU/GPU combination with good affinity (as reported by DCGM) and if there is no suitable CPU/GPU combination available, Univa Grid Engine will schedule the job without binding any CPU cores. A job with -l GPU=1[affinity=true] or -l GPU=1[affinity=1] will not be scheduled if no GPU/CPU combination with good affinity is available.

4.3 Full List of Fixes and Enhancements

4.3.1 8.6.0 (and Also Fixed for a 8.5.*, 8.4.*, 8.3.* Patch Release)

GE-3721 qstat -j "*" -u "user1" is not working
 GE-5290 qstat (-xml) does not accept filter switches when -j "*" is specified
 GE-5831 UGE REST Server Crashing when POSTing new complex
 GE-5941 renewing certificates makes sgepasswd file unreadable
 GE-6575 stree-edit utility broken
 GE-6697 qstat -j "*" does not support "\$user" placeholder set in sge_qstat request file
 GE-6734 wrong scheduler info messages shown for jobs
 GE-6764 very long dispatching time due to RQS rule result in scheduler timeout
 UWSA-77 Basic authentication fails under solaris frequently
 UWSA-81 Add support for listening only on localhost
 UWSA-169 REST Service: 'none' auth method doesn't work
 UWSA-186 requested jobEnvironment is not shown in jobs
 UWSA-188 jobEnvironment ugerestsdk contains error in json converter
 UWSA-189 ugerest is showing same scheduler conf twice
 UWSA-190 upgrade of restlet-jse-2.3.6 to restlet-jse-2.3.10
 UWSA-199 UGERest and other jar files do not show their build version
 UWSA-200 Add version info route to ugerest

4.3.2 8.6.0 (and Also Fixed for a 8.5.* and 8.4.* Patch Release)

GE-4389 enhance qsub man page with JSV modification examples for core binding
 GE-5835 long scheduling times with wildcard PEs and resource reservation
 GE-6018 Setting limits based on percentage.
 GE-6103 jobs are bound to cores even if no binding is requested
 GE-6356 drmaa2_j_get_info does not provide full job information
 -> not all fields are filled
 GE-6402 Scheduler might not respect RQS limits during the time RQS rules are changed
 GE-6432 qdel -u "*" is only allowed to managers, not to operators
 GE-6462 on native Windows (win-x86), environment variable values containing an equal sign are truncated
 GE-6478 Very long load value of loadsensor causes segfault of execd
 GE-6510 Core binding: striding-strategy counts needed cores wrong and rejects viable hosts
 GE-6511 gdi_request_limits does not behave as documented
 GE-6534 sge_execd crash with core dump with GPGPU jobs
 GE-6568 Allow for forced job deletion through UGE REST
 GE-6595 Docker interactive job can't be deleted by qdel
 GE-6671 sudo requests for same user as ugerest service user are rejected
 GE-6682 exec host cannot startup if no admin or submit host

GE-6709 huge virtual memory requirements with test DRMAA1 application
 GE-6728 sched_conf.5 man page is inaccurate regarding the
 PREFER_SOFT_REQUESTS scheduler param
 GE-6771 qsub -sync stops immediately on native Windows (win-x86)
 GE-6787 qmaster and execd logging "invalid value (33026) for ar->op"
 GE-6855 sge_qmaster abort() with critical logging "got NULL element
 for RUE_utilized_now"
 GE-7237 UGE qmaster daemon may crash in 'lo_thread' thread
 GE-7240 UGE qmaster does not handle LO delete cluster request
 UWSA-193 additional job usage values for execd_params
 ENABLE_MEM_DETAILS=1 are missing

4.3.3 8.6.0 (and Also Fixed for a 8.5.* Patch Release)

GE-285 allow parallel job allocation scheme be specified at submission time
 GE-3146 backfilling a resource reservation before a calendar or an AR is broken
 GE-4305 Better documentation for basic share tree use case
 GE-4726 adding a way that multiple jobs can be bound to the same socket
 using all cores
 GE-5436 qmon should not reset value "-1" for sharetree usage_weight_list list
 GE-5569 native Windows (win-x86) sge_execd exits if it cannot access the
 act_qmaster file
 GE-5636 qmaster error logging "rc_add_job_utilization 0 slot amount" indicates
 wrong job reservation
 GE-5650 with allocation rule \$fill_up, slave resource requests are not obeyed
 when master resource and queue requests are provided
 GE-5806 parallel jobs might not startup due to wrong RQS calculations
 GE-5830 Scheduler fails to handle a job submitted with option "-mbind cores"
 GE-5848 allow to use UGE cgroups in Docker jobs
 GE-6020 allow native Windows (win-x86) functions to retry to logon users
 several times
 GE-6105 RSMAP attributes should support per slot resource allocation for PE jobs
 GE-6183 sge_shepherd sets limits too high for master task
 GE-6236 accounting file broken on Solaris if accounting line has 1023 characters
 GE-6237 jobs are being restarted even if the '-r no' was specified
 during submission
 GE-6270 allow to run prolog etc. as root inside a Docker container
 GE-6271 sge_container_shepherd fails if the prolog is started as root
 GE-6407 add documentation for config-api
 GE-6413 shepherd does not handle all error responses to a pull Docker image request
 GE-6434 incomplete binding requests shown in qstat for long lists of binding requests
 GE-6454 improve documenation of Docker integration
 GE-6480 wrong/missing error messages and wrong exit status when initializing
 invalid RSMAP ranges
 GE-6483 document placeholders in Docker requests in the UserGuide and man pages
 GE-6489 using of external loadsensors might deadlock execution daemon
 GE-6490 load sensor specific errors are not logged into execd messages file
 GE-6493 RSMAP map entry selection request does not work

- GE-6497 support halftime -1 setting in scheduler config to disable past usage for sharetree
- GE-6506 qstat does not show granted PE
- GE-6508 Accounting shows wrong fail and exit states for 'qdel -f jobID'
- GE-6521 Qmaster Crashes with LO Enabled and Job Dependencies
- GE-6524 AR shouldn't be scheduled to unknown queue instances at time of submission
- GE-6527 document qsub -xd --help
- GE-6528 allow to specify arguments to autostart Docker jobs
- GE-6536 No error message when a job cannot get scheduled due to RSMAP-ranges
- GE-6537 Submitting RSMAP-range jobs via -adds is broken
- GE-6549 qstat/qhost outgoing packet size is much bigger than the data which is finally displayed
- GE-6553 RQS limits incorrectly applied when PE job submitted with "-l h=<host>"
- GE-6566 qsub rejects valid RSMAP resource requests
- GE-6569 Allow for Deletion of non jobsession jobs in DRMAA2
- GE-6573 reduce resulting qhost client requested data sizes transferred via network
- GE-6583 scheduler is wrongly skipping hosts or queue instances for parallel jobs that are using master task specific requests
- GE-6597 execd uses 100% CPU if it can't delete a finished Docker container
- GE-6615 enhance error logging if load sensor cannot be started
- GE-6617 provide workaround in native Windows (win-x86) sgeexecd.bat script for start /b bug on Windows 10, version 10.0.15063
- GE-6618 native Windows (win-x86) execution daemon crashes if qloadsensor does not work
- GE-6620 error messages from qloadsensor.exe (win-x86) are not forwarded to the execd messages file
- GE-6623 add the UGE admin user to the Performance Monitor Users group on native Windows 10 (win-x86)
- GE-6629 qhost NSOC and NCOR incorrect on lx-arm64
- GE-6637 using hostgroups in rqs limit definition can trigger short qmaster hang at startup or rqs modify request
- GE-6640 qloadsensor.exe report "no error" if an error occurs while initializing the PDH service
- GE-6644 any epilog SIGSEGVs and sets queue in error state with `execed_params INHERIT_ENV=false`
- GE-6664 When host aliases are configured `qsub -sync y` reports "commplib info: successfully updated host aliases (add: 0, del: 0)"
- GE-6665 while a non allocated reservation is "active" in a standing reservation jobs submitted into the SR get rejected
- GE-6670 The global configuration parameter "gdi_request_limits" not working for aliased hostnames
- GE-6678 Improve `accept()` handling in commplib
- GE-6687 RSMAP-topology-masks jobs and -binding jobs result in wrong scheduling decisions
- GE-6695 `qrstat` does not output `cal_depth` and `cal_jump` information for standing reservations
- GE-6696 `save_sge_config.sh` needs to dump advance/standing reservations for upgrade to newer versions
- GE-6706 unexpected logging and possibly incorrect accounting if multiple

- array tasks of a job are running on a host
- GE-6713 shadowd on Solaris cannot start sge_qmaster
 - GE-6737 queue calendars closing queues not considered when max_reservation > 0
 - GE-6739 Parallel job requesting pe range not scheduled even if resources available
 - GE-6741 jobs submitted into AR with RSMAP resources are not scheduled
 - GE-6744 qrstat does not output queue request (-q) and immediate request (-now y)
 - GE-6746 support a "pack socket" core binding strategy
 - GE-6754 Adding new session (qconf -asi) not working on admin only host
 - GE-6755 save_sge_config.sh does not dump all advance/standing reservations
 - GE-6774 Jobs do not get the correct binding when a specific RSMAP id with topology mask is requested
 - GE-6775 RSMAP ids are granted even if the requested cores are already in use
 - GE-6777 huge erroneous reader thread logging at calendar state transition
 - GE-6782 qstat -njd is not working as documented in the man page
 - GE-6785 Supplementary groups in manager and operator lists are ignored during access validation for job deletions.
 - GE-6786 false logging for 'qmaster_params': 'gdi_timeout', 'gdi_retries' and 'gdi_ping'
 - GE-6788 qmaster logging about receiving older load report
 - GE-6796 Calendar modification/state transition might cause repeated timed calendar events for up to one second.
 - GE-6799 unexpected logging messages in sge_qmaster messages file
 - GE-6800 implement a per task prolog and epilog for tightly integrated parallel jobs
 - GE-6812 started docker job at execd may result in sge_shepherd process eating up all memory
 - GE-6814 removing non "lo_*" complex entry triggers error logging of lothread
 - GE-6818 error logging: getgrgid(...) failed: Numerical result out of range
 - GE-6826 Spaces within a comma separated list of switch arguments are not allowed
 - GE-6829 disallow mapping /etc/passwd and /etc/group into the container if AUTOMAP_CONTAINER_USERS=PERSISTENT is specified
 - GE-6835 update host configurations for changed hostnames not working if a changed hostname is matching as substring of another host
 - GE-6836 improve execd reconnect behavior after qmaster shutdown and restart
 - GE-6841 allow to configure the Docker daemon communication timeout
 - GE-6843 Integration with latest Docker CE version(17.09)
 - GE-6852 interactive Docker jobs take very long to finish if the qrsh client is killed and an epilog is configured
 - GE-6853 Sometimes not able to delete pending job if docker device-mapping is used
 - GE-6862 Release notes contain 'current version' also for features that were introduced with FCS
 - GE-6869 arch script does not support Mac OS X High Sierra
 - GE-6874 normal docker job required no_root_quash if execd spooling directory shared via nfs
 - GE-6884 qconf help menu lists ss switch twice
 - GE-6901 "messages" file can have the name ".<digit>" instead of "messages" in case of file creation issues
 - GE-6907 Allow to specify allocation rule (-par switch of qsub) via JC's
 - GE-6913 expose scheduler thread ID in the qping output
 - GE-6916 sge_ca script does not show output for skip install question if CA

- directories are already existing
- GE-6924 PE jobs that request a combination of consumable HOST/JOB and YES RSMAP complexes might not get the correct amount of ids assigned
 - GE-6931 the main shepherd of an interactive Docker job uses 100% CPU and doesn't end if output file is deleted
 - GE-6932 child shepherd waits infinite for mutex in shepherd_trace()
 - GE-6934 jobs that are submitted into AR and request RSMAP ids block ids that were not assigned
 - GE-6939 very long ticket calculation times for parallel array tasks
 - GE-6945 cannot create AR for queues with jc_list "ANY_JC"
 - GE-6946 Delete an array task will break the -tc <number> condition
 - GE-6948 parse error message from Docker response and provide it as job error reason
 - GE-6959 sge_execd calls sched_setaffinity function repeatedly
 - GE-6972 Problem with gridengine/kernel
 - GE-6973 Problem with gridengine/kernel
 - GE-6974 Problem with gridengine/kernel
 - GE-6983 if job is killed by execd enforced limit the job failed state in accounting file should reflect this
 - GE-6997 the native Windows (win-x86) execd should log that it cannot find or start the qloadsensor.exe
 - GE-7002 test Docker integration with Docker versions up to 17.12
 - GE-7008 Jobs requesting RSMAP complexes that are defined without Ids are not scheduled
 - GE-7009 no job dispatching with max_reservation > 0 and consumable+PE+binding combination request
 - GE-7027 In AFS/KRB Grid Engine installations coshepherd/set_token_cmd is not cleaned up
 - GE-7039 AR slot oversubscription
 - GE-7042 Resource reservation due to start time prevents dispatching the next job of the same category
 - GE-7056 Failed/deleted docker interactive job's shepherd remains and increase trace file forever
 - GE-7060 Possible crash of qmaster clients
 - GE-7062 reservation for PE jobs with RSMAP requests is too far in the future
 - GE-7063 submitting an AR to a PE can violate the PE's fixed allocation rule
 - GE-7067 jobs with reservation and RSMAP complex requests cause error logging in qmaster messages file
 - GE-7068 PE jobs that request binding and RSMAP complexes defined as consumable HOST might not be scheduled
 - GE-7069 running jobs requesting host level consumable prevent ARs to be scheduled
 - GE-7078 ARs not backfilled with backfilling=h_rt
 - GE-7085 Logging of PDC create execd message owned by root user
 - GE-7108 CRITICAL "error: lGetElemStrFirst(ST_name): run time type error" when submitting advance reservation with project
 - GE-7111 CSP effective secret key algorithm is not used correctly
 - GE-7112 qmaster error logging "rc_add_job_utilization 0 slot amount (job <job_id> obj global type RUNNING)"

GE-7144 UGE 8.5.5 grid master continuously segfaulting
 GE-7184 provide host level configurable job umask setting
 GE-7187 epilog scripts are not always executed when running docker job
 GE-7263 unset closed file pointers after call to sge_peclose()
 UWSA-194 JobClass name of submitted job is missing
 UWSA-195 fix the OpenSSL security warning

4.3.4 8.6.0

GE-168 enhance qacct [-A account_string] to qacct [-A [account_string]]
 GE-639 job umasks should be configurable per job
 GE-1969 qconf -me reports success on incorrect file
 GE-2186 schedd job info shows old and outdated message although
 job is meanwhile running.
 GE-2242 Inadequate job_info messages for resource quotas with
 parallel jobs
 GE-2464 schedd_job_info can cause immense memory consumption
 GE-2739 No way to remove a -notify flag, once it was set
 GE-2748 Jobs with no suitable queues at all should be easier detect
 GE-3279 Description of 'job_is_first_task' in `man sge_pe` should be rephrased
 GE-3614 add a way to distribute a parallel job on different
 sockets without knowing the exact architecture on
 submission time
 GE-3621 add a placeholder for the -binding parameter which
 aligns the amount of slots with the amount of requested cores
 GE-3754 write documentation for sge_share_mon
 GE-3787 string load values are reported only up to 1024 characters
 GE-3803 qacct failes with accouting files bigger than 4GB on
 native Windows (win-x86)
 GE-3864 qsub -w e/-w v do not consider attributes which are load
 values only
 GE-3965 qalter -w p of a job in user hold prints 'verification:
 job is already running'
 GE-4028 DOS CR-LF in submitted scripts causes shell search errors
 GE-4059 qalter -clearp silently exits
 GE-4275 qalter -w e|w|v|p <job_id> identifies jobs as running when
 they are not eligible for scheduling
 GE-4358 misleading diagnose message for qalter -w p that refers to
 queue 'global' instead of host
 GE-4429 Improve qalter -w option documentation
 GE-4430 Qalter -w p on a held job says 'job is already running'
 GE-4433 qalter returns nothing when run without a job
 GE-4498 man lacks detailed information about the new pss, rss,
 smem, vmem values
 GE-4678 job class parameter V does not work like descibed in
 sge_job_class man page
 GE-4733 finding rqcs excluded queues is printing a useless
 error message

- GE-4734 reduce impact of qalter -w p on sge_qmaster operation
- GE-4785 qmod -rq can trigger a qmaster crash when the queue is in o state
- GE-4793 qalter -tc messages are not displayed, each time of execution
- GE-4794 Information about the setting of tc switch can not be retrieved
- GE-4817 Add automatic corebinding magnitude selection when used with PE's
- GE-4820 Document the '-w' Options to qsub as a way to validate job submissions
- GE-4825 provide Python binding for JSVs
- GE-4839 rescheduling might produce unexpected error messages
- GE-5069 new binding strategy "linear_socket" instead of requesting "linear" plus -l sched_binding_per_socket=1
- GE-5084 qmaster_params "OLD_RESCCHEDULE_BEHAVIOR" should not be declared deprecated
- GE-5100 forwarding of job error messages from native Windows (win-x86) exec hosts to qmaster
- GE-5248 remove deprecated gdi_multi_read_req setting
- GE-5281 Add support for devices subsystem in cgroup integration
- GE-5304 bug in mirror interface causes segfault in drmaa2 application
- GE-5395 adding a way for listing the state of all global resources
- GE-5403 Job should run on free core first
- GE-5471 Need tool to provide overview of used and requested cluster resources
- GE-5535 enable schedd_job_info for specific jobs only
- GE-5537 standing reservation, which enhances the AR
- GE-5542 request for a rerun limit for jobs
- GE-5571 qalter -w e|v|p does not take RQS limit rules into account that contain job class filters
- GE-5573 scheduler triggers job delivery before complete execd cleanup of rescheduled job
- GE-5606 pe_hostfile documentation is not exact enough
- GE-5686 prolog/epilog race conditions when jobs are rescheduled
- GE-5691 qrsh -cwd is broken
- GE-5706 gdi_request_limits parameter is missing in global config
- GE-5725 upgrade procedure fails if LO_ROOT is set
- GE-5733 job in hold state gets tickets and is reported as running by "qalter -w p"
- GE-5773 Ability to change the cgroup name 'UGE' to another name
- GE-5799 Deliver Univa Grid Engine software as RPMs
- GE-5857 handle delete requests of event clients preferred
- GE-5872 gdi_request_limits should support to limit event client registrations
- GE-5888 resources defined in the global host are not available for -masterl requests
- GE-5910 make DRMAA2 compatible with the AR object changes
- GE-5911 make WebService API compatible with the AR object changes
- GE-5919 correct sge_diagnostics man page header and footer
- GE-5924 Standing Reservation XML output
- GE-5926 Standing Reservation must go in Error state when no more allocations are possible

- GE-5927 support to upgrade standing reservations
- GE-5928 support Python configuration API for standing reservations
- GE-5939 reimplement manual rescheduling done by qmod -r
- GE-5947 drmaa2 complete reservation session features
- GE-5956 re-connect request for an event client even on qmaster shutdown
- GE-5963 qalter -w p doesn't report correctly when -masterl switch is used
- GE-5987 examine fopen() system call problem
- GE-6014 Enhance sge_diagnostics man page with info about scheduler profiling
- GE-6038 schedd_job_info true/false is not case insensitive
- GE-6071 Support for Affinity/Anti-Affinity in UGE
- GE-6086 Fix Java code (JGDI, UGEREST etc.) to support standing reservations
- GE-6125 for demo binaries the version string printed by -help command line option and in messages files should contain "demo"
- GE-6129 update BerkeleyDB to version 6.2
- GE-6141 DRAMA2 still does not use GDI sessions which will have an impact on performance
- GE-6143 qalter -w p requests are executed by worker threads
- GE-6147 category string should be created and normalized in qmaster thread when jobs are added or modified
- GE-6159 add qalter to modify end time of Advance Reservations
- GE-6249 remove qtcsh from distribution
- GE-6255 execd job reports get lost due to a race condition in sge_qmaster
- GE-6256 Parallelize sorting in CULL to improve scheduler performance
- GE-6260 Compression/uncompression of data passed/received from commlib layer
- GE-6261 event_master thread performance might be improved by processing events for different event clients in parallel
- GE-6275 Determine number of unused cores (threads) in qmaster and execd
- GE-6277 Improve performance of basic CULL functionality
- GE-6287 Move scheduler category to master
- GE-6328 out-of-the-box functionality to show utilization of global variables
- GE-6334 hostgroup changes via -*attr do not update queue instance settings
- GE-6339 QERROR message should include task ID for array jobs
- GE-6364 check if username needs to be part of the scheduler category string
- GE-6412 deny job submission with empty non boolean request
- GE-6415 core binding jobs fail to be scheduled on free cores.
- GE-6418 Implement host_sort_formula in schedd configuration object
- GE-6424 Adapt config API to reflect object changes
- GE-6439 possible performance degradation in scheduler when debiting dispatched jobs
- GE-6440 create and maintain affinity cache in worker / scheduler thread
- GE-6441 output affinity information with qstat -F and qhost -F

- GE-6450 change naming scheme of fallback messages files
- GE-6455 Look at all open, fdopen, close, etc. calls and map them to a global function
- GE-6458 qconf -srqsl and other "show list" options report an error if no data is configured
- GE-6468 Introduce and document new parameter that influences host resolving timeout handling
- GE-6476 Enhancing sge-diagnostic man page
- GE-6482 scheduler profiling does not cover full scheduler code
- GE-6484 Wrong/missing error-logging for loadsensors
- GE-6491 affinity shall only be reduced for preempted jobs for complex variables which are preemptable
- GE-6492 change host and queue sorting in scheduler thread to reflect affinity
- GE-6494 Wrong binding-parameters are logged in qmaster-messages file instead of sent to client
- GE-6499 Add entry for "used_slots" to sge_pe man page & admin guide
- GE-6500 fix compensation_factor description in sched_conf(5)
- GE-6526 Excessive Memory Usage with large RSMAP Ranges
- GE-6530 Core binding: Binding request for PE-jobs should be "per task" instead of "per host"
- GE-6531 Core binding: execd applies granted core-binding for PE-jobs in a wrongish way
- GE-6532 Core binding: Create new binding strategies with better names
- GE-6533 Core binding: Number of granted cores should be part of accounting
- GE-6538 Add RSMAP-ranges as <name>:<amount> to a host does not work
- GE-6540 remove queue_sort_method from scheduler config (replaced by weight_queue_seqno)
- GE-6544 Core-binding: qsub checking of binding-strategy is not strict enough (linearasdf:4 is accepted)
- GE-6545 adapt Docker version check functions to new Docker version scheme
- GE-6561 Core binding: Remove scheduler parameter "sched_binding_per_socket"
- GE-6567 ranges in combination with RSMAP id requests do not work
- GE-6578 Duplicate calendar entries associated with host_aliases
- GE-6600 Core-binding: cgroups with PE-jobs not correct
- GE-6611 build unsupported platforms with classic spooling support only
- GE-6622 Order of fields in the accounting man page does not match qacct output
- GE-6638 accounting(5) man page field description is broken for "ioops"
- GE-6642 operators cannot delete a (standing) reservation
- GE-6646 Add support for NVIDIA DataCenter GPU Manager
- GE-6647 Automatically use affinity for GPU and CPU where possible
- GE-6649 Use environment variable CUDA_VISIBLE_DEVICES to hide disabled GPUs
- GE-6655 Document how to tag CPU cores as 'already in use' so that they will not be considered for core and memory binding
- GE-6666 qhost man page is lacking description for resources that are free-but-still-bound
- GE-6677 DRMAA jobs submit always with -w e which has a negative performance impact on qmaster

- GE-6691 support halftime -1 setting in scheduler config to disable past usage for sharetree
- GE-6692 cleanup of CULL for halftime -1 that requires minor release change
- GE-6693 allow to set halftime to -1 in qmon/config API and UGE Rest
- GE-6707 qalter -w e|w does not return a validation message.
- GE-6708 qping and other uge binaries dump core if local hostname is not resolveable
- GE-6720 calender off times not considered by resource reservation
- GE-6736 Remove Solaris dtrace support and related things from UGE and LO
- GE-6738 drmaa2_open_jsession does not recreate htable of job, jtemplate and jinfo
- GE-6752 update jemalloc to current version (5.1.0)
- GE-6753 update hwloc lib to current version (1.11.7)
- GE-6758 switch to a newer OS (e.g. CentOS 6) for the lx-* build
- GE-6761 qrstat -ar <ar_id> prints the PE request as granted_parallel_environment
- GE-6766 xml schemas need to be verified, updated and made UGE version specific
- GE-6772 update man page for queue initial_state to include qmaster migration scenario
- GE-6781 qstat -j reports job as running but shows also schedd job information why the job cannot be started
- GE-6783 shepherd trace file grows too large for interactive Docker jobs
- GE-6831 Alternative solution to limit the number of event clients in use by abusive users
- GE-6834 unexpected logging on rescheduling of tight pe jobs
- GE-6837 config-api test in master branch fails due to missing field per_pe_task_prolog
- GE-6839 sge_execd is not properly handling short outages of sge_qmaster resulting in delayed reporting of load values
- GE-6840 Generate all nroff man pages from markdown source files
- GE-6854 pe_n, pe_min_X, pe_max_X missing in jsv(1) man page
- GE-6857 requesting RSMAP complexes as soft request with -soft and/or l_soft does not work
- GE-6859 qacct -A does not show column name with account string
- GE-6860 Implement a way to disable the chaining of RSMAP ids
- GE-6887 reduce the number of copy operations done in event master thread when distributing events to clients
- GE-6891 qalter -clearp does not provide a proper response message
- GE-6902 enable immediate load report sending
- GE-6903 improve communication connection shutdown and gdi timeout handling
- GE-6917 chaining of multiple RSMAP complexes with XOR parameter does not work
- GE-6918 it is possible to specify invalid PE allocation rules
- GE-6919 config-api missing field
- GE-6920 update openssl library to most current version
- GE-6923 Add job category field to 'qstat -j' output
- GE-6947 show user name trying exceed max_u_jobs on qmaster message log
- GE-6955 cgroups definition of subdir_name only working if beginning with "/" on some docker versions
- GE-6982 accounting should contain the pe task id for tasks of tightly

- integrated pe jobs
- GE-6991 extend monitoring to track time waiting in mutex_lock
- GE-6993 environment of Docker pe task shows wrong RSMAP ids if complex is consumable YES
- GE-7001 wrong behaviour if RSMAP topology mask does not fit on actual host topology
- GE-7017 support XOR RSMAP request per PE task only
- GE-7020 Enhance current commlib message protocol to support compression
- GE-7026 build process for markdown man pages is broken
- GE-7031 display requested RSMAP selection in qstat -j/qstat -r
- GE-7038 enhance qping to show compressed data size if applicable
- GE-7041 qalter might cause error message and reject the modification if combined with -w
- GE-7045 backup might fail with "mv: cannot move ... File exists"
- GE-7054 Integrate zlib into build process
- GE-7057 Rescheduling due to preemption does not respect force-switch
- GE-7058 make compression configurable
- GE-7064 SGE_HGR_ variables are set to wrong values when consumables are requested via -masterl and -l
- GE-7065 debiting of PE jobs is wrong if they contain a "-masterl" request
- GE-7099 correct the message displayed during upgrade procedure
- GE-7122 write -xd parameters into job config for non docker job
- GE-7134 update berkeley db libs to current version (6.2.x)
- GE-7135 update postgresql libs to current version 10.x
- GE-7146 mbind nlocal not functioning properly (even in 8.6.0)
- GE-7159 Increase performance of worker threads for job delivery
- GE-7177 integrate performance tools support for UGE/LO build process and TS
- GE-7179 optimize RQS code that consumes much cpu time in parsing for lWhere
- GE-7180 optimize scheduler runtime by optimizing CULL functions and other low level UGE functions
- GE-7185 AR verification of jclass parameter is either missing or does not handle special keywords
- GE-7190 update nvidia cudatoolkit used for cuda_load_sensor to current version
- GE-7197 interactive Docker jobs do not end if the docker container is killed and no input is provided to the qrsh client
- GE-7202 category string in accounting file is wrong for RSMAP requests
- GE-7205 greedy RR: job is backfilled although it should not
- GE-7206 greedy RR: qstat -rr shows negative job ID
- GE-7225 remove GUI installer from distribution packages
- GE-7234 cgroups support does not work with Docker 1.13.1-63 provided by CentOS
- GE-7245 Can't update from 8.4.5 to 8.5.5 with CSP configured
- GE-7249 The qacct -A switch is showing wrong values
- GE-7250 restarting sge_qmaster with bdb spooling invalidates sharetree node ids in qconf -sstree output
- GE-7252 No config-update for execution daemons if reader threads are disabled
- GE-7275 wrong handling of thread local storage can trigger crash on qmaster shutdown
- GE-7281 qalter -V exit code is incorrect when environment variables like LD_LIBRARY_PATH are set

GE-7282 performance degradation in scheduling of parallel jobs
 UWSA-86 authentication issues with RESTapi
 UWSA-149 get jobs call hangs for ugerest
 UWSA-192 REST should handle multiple simultaneous requests of addJob
 UWSA-201 Resource usage not reported for pe jobs via ugeREST

4.3.5 8.6.1

GE-6950 A Docker job requesting duplicate mount points sets the host in error state
 GE-7285 Make python-JSV work with version 2 and 3
 GE-7290 qconf -sconf requires manager privileges
 GE-7328 qstat -r is showing wrong values for requested resources
 UWSA-206 ugerest api is failing with TLS memory allocation error

4.3.6 8.6.2

GE-7350 jobs are no longer started after having been modified via qalter by job name
 GE-7354 do not use jemalloc on lx-arm64

4.3.7 8.6.3

GE-5257 Customer would like back the -binding option for qlogin
 GE-6053 for docker jobs need to create additional binds
 GE-6207 qstat -j<multiple_job_ids> prints all reservation times of all jobs for every job
 GE-6542 A more detailed 'Best-Fit' example should be added to the admin guide
 GE-6813 removed unresolvable admin and submit hosts re-appear after qmaster restart with BDB spooling
 GE-6848 qconf -sds should also show cluster queues that have no queue instances
 GE-6890 for Docker jobs and execd spooling on root_squash too many files have write permissions for others
 GE-7055 Support docker run --env option by qsub -xd for docker container job
 GE-7089 support bulk changes for exec host and project objects
 GE-7096 support for nvidia-docker 2.0
 GE-7142 qstat -j shows env=NONE for jobs submitted with variable without value (-v var=)
 GE-7335 execd crash due to expand_path ~ instead of ~/
 GE-7345 lothread should wait for lodail to be ready before sending state changes
 GE-7349 description of DISABLE_NAME_SERVICE_LOOKUP_CACHE in sge_conf is incorrect
 GE-7351 sge_shepherd stays running if Docker job is deleted

GE-7365 RSMAP-request with XOR does not work when RSMAP is defined with a range
 GE-7367 gdi_request_limits doesn't work as documented for qmod requests
 GE-7370 support Docker up to version 18.06
 GE-7373 formatting issues with some man pages makes option search impossible
 GE-7382 cgroup subdir_name cannot always handle subdir-structures
 GE-7390 qselect with RSMAPs returns no queues or strtok errors
 GE-7395 SGE_HGR_TASK variable should also be exported for non PE jobs
 GE-7400 (Re)opening BDB database might fail without corresponding logging in the message file
 GE-7407 timer for job cleanup of tightly integrated job not setup on qmaster restart
 GE-7408 timeout handler for cleanup of tightly integrated job must request global lock
 GE-7409 no setup of queued signal handler for jobs at qmaster restart
 GE-7410 no error message if qselect is used with -l without a value
 GE-7412 qmaster is not accepting new RW requests
 GE-7414 SGE_HGR_TASK_ variable is exported for jobs that request RSMAPs as soft request but don't get any
 GE-7418 added more logging information for job report handling
 GE-7423 reaching reschedule limit for job crashes qmaster
 GE-7427 inst_sge -upd-ars fails on Ubuntu Linux
 GE-7429 qmaster crash in commlib

4.3.8 8.6.4

GE-4340 enable -V switch for qrsh (without command) and qlogin command
 GE-5805 Provide limit to 'exit 99' re-scheduling attempts
 GE-6235 Provide a way to change execd startup behaviour -> infinite connection retries
 GE-6451 sge_do_log() function doesn't try to write a panic file if logging to the messages file is not possible
 GE-6473 sge_share_mon issues
 GE-6512 implement a way to suppress the user switch inside docker images for docker jobs
 GE-6650 Make GPU affinity manually configurable
 GE-7036 more info on qmaster message log when -tcon yes for non array job
 GE-7088 add a CLIENT_COMMAND parameter to JSV
 GE-7209 named pipe execd-shepherd file descriptor leak
 GE-7271 support to set "loglevel" in local cluster configuration
 GE-7310 ensure UGE compatibility with DCGM versions up to 1.4.6
 GE-7337 -xd --shm-size doesn't work correctly
 GE-7359 More information in qmaster message log when job request invalid host
 GE-7388 "commlib returns can't find connection" errors for "qsub -sync" jobs
 GE-7438 frequent logging of "deletion of one or more tasks skipped for job..." in qmaster messages file
 GE-7440 add support for -umask switch to qrsh

GE-7442 jobs get RSMAP id assigned if -l rsmmap=0 is requested
 GE-7446 cgroups: Some slave-tasks might not get started in cgroup on a host
 GE-7447 rpm package ugerest openjdk dependency fails
 GE-7450 qmon does not show qinstances anymore
 GE-7454 Allow a job to identify how often the job was executed in the past
 GE-7455 rescheduling: rerun_limit does not work with "exit 99"
 GE-7457 add execd_param to disable docker image check in sge_execd
 GE-7458 Docker jobs are not rescheduled on exit 99
 GE-7462 qconf -Ae <directory> failed with internal error messages
 GE-7468 RQS report value double than what actual usage
 GE-7478 generation of debug information when modifying host groups might impact performance
 GE-7481 Combine processor reports and exec host load reports
 GE-7485 optimize performance of modification of host groups (qconf -Mhgrp)
 GE-7486 optimize performance of exec host deletion
 GE-7497 improve scheduling time for clusters having slots defined on exec host level
 GE-7509 queue initial_state=disabled should not disable queue after qmaster restart/migration
 UWSA-208 ugerest configuration is partially destroyed when running distinst
 UWSA-210 libjgdi.so reports undefined symbol: rsmmap_request_to_string
 UWSA-211 load_values do not show up in uge rest api call execheosts/global

4.3.9 8.6.5prealpha_devbuild_1

GE-4575 deleting array tasks can block qmaster for a significant time
 GE-4638 showq does not take d_rt into account
 GE-4823 Missing header in sge_conf(5) for cgroups killing parameter
 GE-5730 support UGE on IBM Power 9 architecture on Linux (lx-ppc64le)
 GE-5912 comma-separated userset-lists are not accepted
 GE-6584 mem_free should be allowed to increase even for running jobs
 GE-6700 low m_mem_free load values prevent job dispatching
 GE-6749 "qstat -s r" is broken for array jobs with suspended tasks
 GE-6750 "qdel -s r" is broken for array jobs with suspended tasks
 GE-6801 accounting man page field description is wrong for "wallclock"
 GE-6805 incorrect booking of consumables results in scheduling errors and massive error logging
 GE-6830 enable RSMAP placeholders to be resolved for -masterl requests, too.
 GE-6832 Add more information from man page to userguide/admin guide
 GE-6863 job with -pty yes failed if output was directed to folder with permission 754
 GE-6958 execd should also cleanup dockers cgroups dir inside cgroups uge jobs dir if not done by docker
 GE-6978 UGE/cgroup leaves orphan processes after qdel if the job is submitted within an tightly integrated openmpi
 GE-6990 DRMAA2 Python binding to support customer workflow
 GE-7244 ensure that all generated man page (not only NROFF) are part of the packages

- GE-7268 projects & xprojects fields in execution host configuration, not allowing comma separated values
- GE-7332 pending job with "-tcon y" and "-t" prevents other jobs from running
- GE-7337 "-xd --shm-size" doesn't work correctly
- GE-7343 add a commlib parameter not to do hostname resolving but parse the ip address out of the hostname
- GE-7383 put all queue instances on host in error state on Cgroups related errors
- GE-7391 PE slave tasks should be handled in own cgroups
- GE-7434 Use OOM Notification API in UGE Cgroups implementation to notify when jobs exceed memory
- GE-7443 'sgeexecd stop' fails if corresponding host is no admin host
- GE-7469 Unable to edit queue slots configuration using qconf -datr
- GE-7475 enhance monitoring information of reader thread that does event processing
- GE-7476 sge_get_config_version_for_host() does hostname resolving which can be avoided
- GE-7482 handle permission check GDI requests in listener thread.
- GE-7483 add a possibility to give manager requests higher priority
- GE-7487 use sge_mutex_lock instead of pthread_mutex_lock in all modules used by sge_qmaster
- GE-7489 improve performance for qmod -rq
- GE-7490 new added execution hosts not handling reschedule_unknown setting
- GE-7492 bad dispatching rate with many big array jobs in a huge cluster
- GE-7495 rescheduling of sequential jobs unnecessarily creates timer events
- GE-7496 enable cgroups based killing for PE tasks
- GE-7499 shepherd should not be part of the memory Cgroup
- GE-7502 add scheduler param to suppress sending of running job tickets
- GE-7503 improve general rescheduling performance
- GE-7504 improve reschedule_unknown triggered rescheduling behavior on massive execution host lost
- GE-7505 add additional worker pool that allows to handle priority requests
- GE-7506 improve performance of adding large number of execution hosts
- GE-7511 newline in jsv_add_env function let qsub crash
- GE-7513 unexpected logging: invalid task number 0 for job ... in "ORT_ptickets" order
- GE-7519 execd might not always send a load report within configured load_report_time
- GE-7520 unexpected connection renewal of execution daemons
- GE-7528 qconf -si sid is ignored if not used as first switch
- GE-7540 jobs do not get the correct binding if affinity is requested and the affinity mask is overwritten with a topology mask
- GE-7546 job cleanup problem for PE jobs at execution daemon
- GE-7550 do not report m_mem_free_nX/m_mem_used_nX as load values
- GE-7556 implement deadlock detection for sge_qmaster daemon
- GE-7574 concurrent array jobs (-tcon yes) get partially started when the number of running tasks exceeds maxujobs
- GE-7586 qmaster becomes unresponsive and needs 100% CPU after qalter

- GE-7592 ensure UGE compatibility with DCGM versions up to 1.5.6
- GE-7594 resources held by a standing reservations are not properly freed when the standing reservation is modified or is deleted after sge_qmaster restart
- GE-7595 standing reservation id restarts at 0 after modifying resource requests with qralter
- GE-7597 resources held by a standing reservations are not properly freed when the complex_values of the queue are modified
- GE-7654 massive logging of "GDI session <string>: created=<nr>, processed=<nr>, required=<nr>"

4.3.10 8.6.5prealpha_devbuild_2

- GE-3942 qmon man page refers to schedd_conf(5)
- GE-3946 Explain priority normalization and fix issues with sge_priority man page
- GE-4020 getservbyname segfaults when called with wrong amount of arguments
- GE-4381 Enhance error message logging for flat file spooling
- GE-4402 SGE_DRMAA_ENABLE_ERROR_STATE variable is not documented in wiki pages
- GE-4469 Need clear description how to handle certificates within UGE CSP installations
- GE-5125 Add addition information in man page for qsub
- GE-5305 jsv does not recognize -now switch
- GE-5346 qdel <jobid> -t <taskid> deletes complete job
- GE-6751 qalter -clearp and -clears doesn't delete "hold_jid" attributes
- GE-7517 queue is set in error state if Docker daemon is overloaded
- GE-7553 SR in error state because past SR instance is in "E" state
- GE-7572 Docker background process doesn't allow to exit the interactive job
- GE-7580 cgroup directory of docker job remains although job finished
- GE-7581 PE job with consumable HOST request doesn't get correct resources if max_reservation is greater than 0
- GE-7587 Fix spelling errors in AdminGuide
- GE-7596 docker -xd command can't export multiple values
- GE-7598 Docker jobs set queue instance in error because permission to write pe_hostfile is denied
- GE-7626 consumable records in the reporting file end with a delimiter (comma)
- GE-7645 job killed by cgroups limit results in zero values for "ru_*" usage fields
- GE-7646 job killed by cgroup OOM notification is pending in "E" state
- GE-7656 need parameter to enable qmaster abort() when a deadlock was detected
- GE-7657 improve deadlock detection reliability
- UWSA-230 Restarting Qmaster Breaks Synchronization With UGEREST

4.3.11 8.6.5prealpha_devbuild_3

- GE-4378 Respect better parsing for admin user in bootstrap file
- GE-5513 "The filename or extension is too long" error when creating job process on native Windows (win-x86)
- GE-5801 Windows (win-x86) qloadsensor.exe doesn't recognize if execd is killed or crashed
- GE-5826 port RESTRING matching to native Windows (win-x86)
- GE-6019 Improve error logging of native Windows (win-x86) RedirectStdHandles() function
- GE-6222 UGE Starter Service of native Windows (win-x86) fails to start second execd if the first cannot be started
- GE-6223 add check to native Windows (win-x86) installer if an execd is already installed to the same \$SGE_CELL or uses the same port
- GE-6226 the native Windows (win-x86) execution daemon doesn't report m_cores, m_sockets and m_threads
- GE-6809 Could not edit non reserved complex when advance reservation with pe is running
- GE-6896 qconf -me parser allows to define a RSMAP twice which cause sequential errors
- GE-7059 qsub job verification "-w e" is executed before server side JSV run
- GE-7323 sgepasswd tool enhancement or change of behaviour
- GE-7623 wrong debiting of consumables with consumable type HOST
- GE-7624 support Docker up to version 18.09
- GE-7641 newlines in qmaster messages file after hold modifications breaks file format
- GE-7697 it is possible to remove a host exclusive consumable from a host which is referenced in an AR
- GE-7698 rqs: wildcard projects with at least two different limits crashed qmaster
- GE-7704 make sure libxml2.dll exists on native Windows (win-x86) exec host
- GE-7705 port work binary to native Windows (win-x86)
- UWSA-223 ugerest should not truncate /tmp/UGERestService0.0.log at startup

4.3.12 8.6.5alpha1

- GE-3938 Man page sge_priority needs prio/pprio clarity
- GE-4391 add more information about the importance of the gid range to the install guide
- GE-4454 The sge_priority man page has a typo regarding prior calculation
- GE-5299 A way to remove hold_jid switch
- GE-6457 log full communication between shepherd and Docker daemon to the shepherd trace file
- GE-6802 job are handled as still running, even if all processes are already stopped
- GE-7028 Completed job remains in dr state and is not cleaned up at execd
- GE-7243 man page qsub -P description incorrect

- GE-7253 errors with consumable capacity management after "qalter -when now" or after reduction of capacity
- GE-7336 typos in AdminsGuideGE, chapter 3.9.5, Tuning the sge_shadowd
- GE-7404 cgroups based devices blocking mechanism does not block all devices
- GE-7606 ./inst_sge -copycerts <hostlist> command line parsing not correct
- GE-7631 Docker -xd doesn't work for --sysctl option
- GE-7664 qloadsensor exe reports wrong core counts
- GE-7674 placeholder '\$' character can't work with double quote("") unlike manual described
- GE-7693 re-schedule standing reservations without allocation or being in error state
- GE-7702 even if it is already installed, native Windows (win-x86) installer always asks for SGE admin user password to install UGE_Starter_Service.exe
- GE-7710 handle leak in UGE Job Starter Service causes start failures of some jobs
- GE-7720 active SR stays in "E" state after qmaster restart even after all execds reconnect
- GE-7724 not all markdown man pages are part of the packages
- GE-7737 qalter -when now might break EXCLUSIVE consumable functionality
- GE-7750 synchronize execd signaler thread with execd main thread
- UWSA-157 Job State can be stale until full job refresh
- UWSA-176 clusterqueuesummary contains null entry when hostlist is NONE in queue
- UWSA-216 Cannot view tasks in Rerun Queue (Rq) State
- UWSA-222 ugerest connection and shutdown issues
- UWSA-224 ugerest does not log its version information at startup

4.3.13 8.6.5alpha2

- GE-6648 Make GPU/CPU affinity a possible hard and soft request
- GE-6652 Implement DCGM callbacks in case of GPU failures
- GE-7362 Document RSMAPs in man-pages and Usersguide, including their request-syntax
- GE-7673 RQS computes double usage for RSMAPs of type HOST for PE jobs
- GE-7748 formatting issue makes subordinate example impossible to read
- GE-7762 ensure UGE compatibility with DCGM versions up to 1.6.3

5 Upgrade Notes

5.1 Upgrade Requirements

This is a summary of the Upgrade Matrix that describes how you can carry out the transition from Sun or Oracle Grid Engine 6.2uX, Univa Grid Engine 8.X.X to Univa Grid Engine 8.6 when you are currently using classic, BDB local spooling or PostgreSQL spooling.

Version	Upgrade Method
Univa Grid Engine 8.X.X	Backup/Restore
Oracle Grid Engine 6.2u6-6.2u8	Backup/Restore
Sun Grid Engine 6.2u5	Backup/Restore
Sun Grid Engine 6.2u1-6.2u4	Upgrade to SGE 6.2u5 and then Backup/Restore
Sun Grid Engine 6.2 FCS	Upgrade to SGE 6.2u5 and then Backup/Restore

Table 13: Upgrading from SGE, OGE, UGE 8.X.X to Univa Grid Engine 8.6.X

6 Compatibility Notes

6.1 Changes in Windows Execution Host sgepasswd File

The encryption algorithm for the “\$SGE_ROOT/\$SGE_CELL/common/sgepasswd” file passwords has been changed from RC4 to AES-256-CBC:

If you upgrade to the current version of Univa Grid Engine you need to convert your existing sgepasswd file during the upgrade procedure.

Become root and execute the following command on the master machine:

```
# sgepasswd -c
```

This will create a backup of your original ‘sgepasswd’ file as ‘sgepasswd.old_algorithm_backup’ and create the new compatible sgepasswd file. Otherwise encryption related error messages may show up.

If you create a new sgepasswd file from scratch no additional steps compared to previous versions are required.

6.2 Scheduler Log File

In previous versions of Univa Grid Engine if both the master and some slave tasks of a parallel job were scheduled to the same queue instance, one line was written to the scheduler log file containing the number of slots that was granted to this job on the queue instance of the master task. Such a line looked like this: 249:1:STARTING:1522328357:2772638938:Q:B@host1:slots:3.00000

From Univa Grid Engine 8.6.0 on, two lines are written, one for the master task, one for the slave tasks: 249:1:STARTING:1522328357:2772638938:Q:B@host1:slots:1.00000 249:1:STARTING:1522328357:2772638938:Q:B@host1:slots:2.00000

This is because of changed handling of the master task which was necessary to fix GE-5888, see the “Fixes and Enhancements” section for details.

6.3 Removed Scheduler-Parameter queue_sort_method

With the newly implemented affinity-feature, the scheduler-parameter `queue_sort_method` has been replaced with the new parameters `weight_host_sort`, `weight_queue_host_sort`, `weight_queue_seqno`. With these it is not only possible to configure a queue-sorting solely based on `seq_no`, or on the `host_load_formula`, as it was with `queue_sort_method`. But it is now also possible to configure a mixed sorting strategy, where the amount of the weight-parameters decide the ratio with which they influence the sorting.

For configuring what used to be `queue_sort_method = load`, one now has to set `weight_queue_seqno` to a significantly smaller number than `weight_queue_host_sort`. For `queue_sort_method = seq_no`, simply set `weight_queue_seqno` a significantly higher value than `weight_queue_host_sort`.

6.4 Changes for qconf Exit States

The qconf will no longer report an error when showing the content of empty configuration objects. If an configuration object contains no elements the exit status of qconf will be 0 and there will be no error message. The change affects following qconf command line options:

- qconf -scall show a list of all calendar names
- qconf -sckptl show all ckpt interface definitions
- qconf -sconfl show a list of all local configurations
- qconf -sel show a list of all exec servers
- qconf -sh show a list of all administrative hosts
- qconf -shgrpl show host group list
- qconf -sjcl show job class list
- qconf -sm show a list of all managers
- qconf -so show a list of all operators
- qconf -spl show all parallel environments
- qconf -sprjl show a list of all projects
- qconf -sql show a list of all queues
- qconf -srqsl show resource quota set list
- qconf -ss show a list of all submit hosts
- qconf -sul show a list of all user set lists
- qconf -userl show a list of all users

6.5 Changes for Scheduler Profiling

The scheduler profiling option is revised and cleaned up. The most important changes are:

- Enhanced sge_diagnostics man page with info about scheduler profiling
- The scheduler profiling table shows new profiling levels: “ticket calculation”, “scheduler thread”, “ssos init”, “config update”, “wait for order completion”, “mirror events” and “set event client params”.
- The scheduler profiling level “pending ticket calculatio” was renamed to “priority calculation”.
- The scheduler profiling level “copy lists” was renamed to “data preparation”.
- The scheduler profiling level “scheduler” was renamed to “scheduling”.
- The scheduler profiling level “wait” was renamed to “waiting for events”.

6.6 Changed Limit Calculations

The resulting limit calculation is revised and fixed. The most important changes are:

- The configured consumable type (NO, YES, JOB, HOST) will have no influence on any resulting limit for tight integrated parallel jobs.
- Previous version calculated the resulting limits by far to high (depending on pe and consumable settings)
- This also affects the cgroups h_vmem observation

Univa Grid Engine versions prior to 8.5.1 showed, by far, a too high limit value setting for limits like e.g. `h_vmem`. The limit adjustments are now adapted. A detailed overview of the limit observation and how it works is described in the `sge_diagnostics(1)` man page (JOB LIMITS).

ATTENTION: If you're updating to 8.6.0 from a previous version it is recommended to verify the used limit requests of your jobs. It might be necessary to change the request value. If the limit is set too low or adjusted to fit the old limit adjustment jobs which were running fine might fail after installing this version.

6.7 New Default for Job Verification of DRMAA Submitted Jobs

In the past a job verification (`-w e`) was triggered for all jobs submitted via DRMAA. This had a negative performance impact on qmaster for all DRMAA submitted jobs which might have had also a negative impact on the cluster throughput. The verification default for DRMAA jobs has now been disabled (`-w n`) for Univa Grid Engine 8.6.0. Users that nevertheless want to get jobs verified can still enable this through the DRMAA native specification.

6.8 Default for Integer Complexes

Older Univa Grid Engine installations allowed to request an integer complex resource during job submission without the need to specify the amount. Implicitely 1 was used when the amount of requested resources was omitted. This is not possible anymore beginning with 8.6.0.

6.9 Deprecated Functionality

'qalter -w p' is deprecated. Instead scheduler job information has to be used.

Starting with 8.6.5 qmaster_param ENABLE_REDUCE_MEM_FREE is deprecated and will be removed with 8.7.0. Decreasing and increasing of mem_free is now possible without any configuration.

6.10 Removed Functionality

Following components/features were removed with version 8.6.0 of Univa Grid Engine:

- Graphical Installer
- qtcsd

6.11 Changed UGERest configuration location

Starting with UGERest 8.6.4 the configuration files are installed into \$SGE_ROOT/\$SGE_CELL/common/ugerest_conf. This is done automatically when using ./install_ugerest script for installation. The reason for this change was accidental overwriting of configuration files when unpacking a patch into an existing installation. If you still need your old configuration files for further reference to existing settings, backup the \$SGE_ROOT/ugerest/conf directory before installing a new ugerest package file.

7 Known Issues and Limitations